View NSN Online: https://aerobasegroup.com/nsn/8010-01-144-9873

Product ID:N-1301A AIRCRAFT RED 31136 MSDS Date:10/06/1991 FSC:8010 NIIN:01-144-9873 Kit Part:Y MSDS Number: BLJNF === Responsible Party === Company Name: NILES CHEMICAL PAINT CO Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Num:616-683-3377 **Emergency P** hone Num:219-236-5956 Preparer's Name: MIKE LICHATOWICH CAGE:02388 === Contractor Identification === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

Ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 71.2 MM @ 20 C) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 16% Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM A CGIH TLV:200 PPM/300 PPM STEL EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTER RESIN Fraction by Wt: 13% Other REC Limits:NONE SPECIFIED

Ingred Name:BARIUM SULFATE CAS:7727-43-7 RTECS #:CR0600000 Fraction by Wt: 12% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PM ACETATE (VAPOR PRESSURE 3.7 MM @ 20 C) CAS:108-65-6 RTECS #:AI8925000 Fraction by Wt: 12% Other REC Limits:NONE SPECIFIED

Ingred Name:BUTYL ACETATE (SARA III) (VA POR PRESSURE 10 MM @ 20 C) CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED OSHA PEL:150 PPM ACGIH TLV:150 PPM/200 PPM STEL EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED INGREDS ARE NOT CONSIDERED HAZARDOUS UNDER FED HAZARD COMM REGULAITONS) Fraction by Wt: BALANCE Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 4.59 LBS/GAL. RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

\_\_\_\_\_

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION, LACRIMATION. SKIN: IRRITATION, DEFATTING & DERMATITIS. INHALATION: NASAL & RESPIRATORY IRRITATION, CNS DEPRESSION. INGESTION: GASTROINTESTINAL IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM, CNS, LUNGS.

Explanation of Carcinogenicity:NOT LISTED BY NTP, IARC, OR OSHA.

Effects of Overexposure:EYES: REDNESS, BLURRED VISION. SKIN: REDNESS. INHALATION: CNS: DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, CONFUSION. NAUSEA, HEADACHE, VERTIGO, POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION. INGESTION: ABDOMI NAL PAIN, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:INHALATION: MOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE ARTIF RESP. GET

MED AID ASAP. SKIN: IMMED FLUSH W/WATER. IF CLOTH CONTAM, REMOVE & FLUSH SKIN W/WATER. GET MED AID. WASH CLOTH/DECONTAM SHO ES BEFORE REUSE. EYE: IMMED FLUSH W/WATER 15 MIN, OCCAS LIFT EYELIDS. GET MED AID IMMED. INGEST: DRINK 1-2 GLASSES WATER. DON'T INDUCE VOMIT. SEE DR/POISON CNTRL CTR IMMED. TREAT SYMPTOMATICALLY.

Flash Point Method:TCC Flash Point:20.0F,-6.7C Lower Limits:1.3 Upper Limits:10.0 Extingu ishing Media:DRY CHEMICAL, FOAM, CO2. Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE (POS PRESSURE MODE) FULL PROTECT CLOTH. WATER MAY BE USED TO COOL CLSD CNTNRS TO PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT. Unusual Fire/Explosion Hazard:VAPOR HEAVY, MAY TRAVEL TOIGNIT SOURCE. CNTNR EXPLODE W/HEAT. KEEP FROM HEAT/IGN SOURCE. APPL TO HOT SRFCS REQUIRES SPCL PRECAUTIONS. DECOMP PROD ARE HLTH HZD.

Spill Release Procedures:SMALL: ELIM IGNIT SOURCE. DON'T BREATH/AVOID SKIN CONTACT. ABSORB W/INERT MAT'L. RECLAIM LIQ/ABSORB INTO RECOVERY/SALVAGE DRUMS. LRG: ELIM IGNIT SOURCE. DON'T BREATH/AVOID SKIN CONTACT. DIKE. RECLAIM INTO RECOVERY/SALVAGE DRUMS/TANK TRUCK-DISPOSAL.

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED

WHEN NOT IN USE. AVOID ROUGH HANDLING. Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS.

Respiratory Protection:WEAR (TC-23C-75) FITTED HALF-MASK/FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTION FOR USE.
Ventilation:PROVIDE SUFF VENT (VOL/PATTRN)-KEEP AIR CONC BELOW TLV/PEL. REMOVE DECOMP PROD (WELD/FLAME CUT). VENT VAPOR FROM BAKING.
Protective Gloves:NITRILE, OR VITON GLOVES.
Eye Protection:CHEM GOGGLES, SAFETY GLASSES, FACE SHLD
Other Protective Equipment:WEAR CHEM RESISTANT (NITRILE, VITON) CLOTHING AS NEEDED TO PREVENT SKIN CONTACT. DON'T WEAR CONTACT LENSES.

Work Hygienic Practices:REMOVE CLOTH THAT BECOMES WET, WASH BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOM.

Supplemental Safety and Health

Boiling Pt:B.P. Text:175 TO 302F Vapor Density:> AIR Spec Gravity:11.20 LBS/GAL Viscosity:70-85 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER. Solubility in Water:SLIGHT. Appearance and Odor:LIQUID, ODOR OF SOLVENT. Percent Volatiles by Volume:64.19

Stability Indicator/Materials to Avoid:YES NITRATES, STRONG

## OXIDIZERS, ALKALIES, ACIDS. Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK FROM DROPPING. Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.