View NSN Online: https://aerobasegroup.com/nsn/8040-00-619-7962

BAKER SEALANTS AND COATINGS CO (CANC. LOCATION UNK -- ADHESIVE PAPER LABEL X-817 -- 8040-00-619-7962

Product ID: ADHESIVE PAPER LABEL X-817 MSDS Date:11/02/1990 FSC:8040 NIIN:00-619-7962 MSDS Number: BLJWB === Responsible Party === Company Name: BAKER SEALANTS AND COATINGS CO (CANC. LOCATION UNK Address:234 SUYDAM AVE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Country:US Info Phone Num:201-333-6986 Emergency Phone Num:201-333-6986 Preparer's Name: CHARLES FRIEDMAN CAGE:34094 === Contractor Identification === Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094

Ingred Name:RUBBER, SYNTHETIC CAS:25038-32-8 Fraction by Wt: 17% Other REC Limits:NONE SPECIFIED

Ingred Name:NAPHTHA CAS:803 0-30-6 RTECS #:DE3030000 Fraction by Wt: 24% Other REC Limits:NONE SPECIFIED ACGIH TLV:500 PPM

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 58% Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ANTIOXIDANT Fraction by Wt: 0.1% Other REC Limits:NONE SPECIFIED

Ingred Name:PLASTICIZER CAS:62258-49-5 Fraction by Wt: 1% Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 705 RTECS # :9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EYES: CAN CAUSE SEVERE IRRITATION. SKIN: CAN CAUSE DERMATITIS. INHALATION: CAN CAUSE RESPIRATORY IRRITATION. INGESTION: CAN AGGRAVATE ABDOMINAL DISORDERS. Medical Cond Aggravated by Exposure:NONE

First Aid:EYES: FLUSH

WITH WATER. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Flash Point:50.0F,10.0C Lower Limits:0.8 Upper Limits:7.1 Extinguishing Media:EXTINGUISH WITH REGULAR FOAM, CO2 OR DRY CHEMICAL. Fire Fighting Procedures:REMOVE ALL IGNITION SOURCES. WEAR SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:KEEP AWAY FROM SPARKS, OPEN FLAME AND

OPEN ELECTRICAL EQUIPMENT.

Spill Release Procedures:LARGE SPILLS: SHOVEL INTO CONTAINERS, PREVENT RUN-OFF TO SEWERS, ELIMINATE ALL IGNITION SOURCES AND NOTIFY PROPER AUTHORITIES. SMALL SPILLS: WIPE UP.

Handling and Storage Precautions: KEEP AWAY FROM SPARKS, OPEN FLAMES; AND AVOID PROLONGED BREATHING OF VAPORS.

Respiratory Protection:AIR SUPPLIED RESPIRATOR. Ventilation:MECHANICAL. Protective Gloves:WEAR RESISTANT GLOVES. Eye Protection:SAFETY GLASSES. Supplemental Safety and Health

HCC:F2 Boiling Pt:B.P. Text:230 TO 288F Vapor Pres:14-23MM HG Vapor Density:> AIR Spec Gravity:.84 Viscosity:12.1 SEC+GH Evaporation Rate & amp; Reference:1-1.9 (BUAC = 1) Solubility in Water:INSOLUBLE Appe

arance and Odor:CLEAR, PUNGENT
Percent Volatiles by Volume:85

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:POSSIBLY CARBON MONOXIDE WHEN BURNED.

Waste Disposal Methods:DISPOSE OF "AS LOCAL, STATE AND FEDERAL REGULATIONS."

Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.