

HERNON MANUFACTURING, INC. -- ANAEROBIC ADHESIVE -- 8030-00-133-3164

=====
Product Identification
=====

Product ID:ANAEROBIC ADHESIVE

MSDS Date:01/01/1987

FSC:8030

NIIN:00-133-3164

MSDS Number: BLKWF

=== Responsible Party ===

Company Name:HERNON MANUFACTURING, INC.

Address:121 TECH DRIVE

City:SANFORD

State:FL

ZIP:32771

Country:US

Info Phone Num:407-322-4000

Emergency Phone Num:407-322-4000

CAGE:D

O346

=== Contractor Identification ===

Company Name:HERNON MANUFACTURING

Address:121 TECH DRIVE

Box:City:SANFORD

State:FL

ZIP:32771

Country:US

Phone:407-322-4000/800-255-3924

CAGE:61603

Company Name:HERNON MANUFACTURING INC.

Address:865 ESSEX STREET

City:BROOKLYN

State:NY

ZIP:11208-5220

Phone:718-649-3000

CAGE:DO346

=====
Composition/Information on Ingredients
=====

Ingred Name:ORGANIC HYDROPEROXIDE

Fraction by Wt: 2%

Other REC Limits:NONE SPECIFIED

Ingred Name:ALKYL ARYLAMI

NE
Fraction by Wt: 0.9%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Health Hazards Acute and Chronic:MAY CAUSE SKIN IRRITATION IN SENSITIVE PERSONS.

===== First Aid Measures =====

First Aid:EYES: IRRIGATE IMMEDIATELY AND THOROUGHLY WITH WATER AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point

t:>200F,>93C

Extinguishing Media:FOAM, DRY CHEMICAL, CO2.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH SPILL AWAY WITH WATER SPRAY. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED SKIN CONTACT.

Other Precautions:STORE BELOW 100 F.

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL: RECOMMENDED.

Protective Gloves:RECOMMENDED.

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: