

BAKER SEALANTS AND COATINGS CO, INC. -- PAINT, OIL, EXTERIOR, CONCRETE --  
8010-00-584-3336

===== Product Identification =====

Product ID:PAINT, OIL, EXTERIOR, CONCRETE

MSDS Date:11/13/1990

FSC:8010

NIIN:00-584-3336

MSDS Number: BLKYM

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO, INC.

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Nu

m:201-333-6986

Emergency Phone Num:201-333-6986/800-356-3129 CHEMTREC

Preparer's Name:CHARLES FRIEDMAN

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

===== Composition/Information on Ingredients =====

=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 26.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 26.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:2 MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:RAW LINSEED OIL  
CAS:8001-26-1  
RTECS #:OI9690000  
Fraction by Wt: 12.0%  
Other REC Limits:NONE SPECIFIED

In  
gred Name:CARBON BLACK  
CAS:7440-44-0  
RTECS #:FF5250000  
Fraction by Wt: 4.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:MINERAL SPIRITS  
CAS:8056-41-3  
Fraction by Wt: 13.0%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:500 PPM

Ingred Name:VOC: 192  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenic

ity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: CAN CAUSE IRRITATION. SKIN: CAN CAUSE DEFATTING. INHALATION: CAN RESULT IN HEADACHE AND DIZZINESS. INGESTION: CAN CAUSE NAUSEA.

Medical Cond Aggravated by Exposure:NONE

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH COOL RUNNING WATER FOR 15 MINS. SEE A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: PROVIDE FRESH AIR AND REST. INGESTION: DO NOT INDUCE VOMITING. DRINK ONE OR TWO GLASSES OF WATER TO DILUTE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:110F,43C

Lower Limits:0.8

Upper Limits:5.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT USE WATER.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS

AND OPEN FLAMES. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY WITH INERT ABSORBENT(S) AND NON-SPARKING TOOLS. SAFELY DISPOSE OF SATURATED ABSORBENT(S) BY IMMERSING IN WATER. WEAR PROTECTIV E EQUIPMENT DURING CLEANUP.

=====  
===== Handling and Storage =====

Ha  
ndling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. KEEP CONTAINERS AWAY FROM ANY SOURCE OF IGNITION.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CANISTER MASK OR AIR PACK IF VENTILATION IS INADEQUATE.

Ventilation:LOCAL: IS RECOMMENDED. MECHANICAL: WITH APPROVED CL D EXPLOSION PROOF MOTOR AND SWITCHES.

Protective Gloves:NEOPRENE RUBBER GLOVES.

Eye Protection:CHEMICAL SAFETY GOGGLES.

Supplemental Safety and Health

==

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:3.1 MM@68F

Vapor Density:3.9

Spec Gravity:1.46

Viscosity:89-104

Evaporation Rate & Reference:0.12 (BUAC = 1)

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK COLOR, PETROLEUM

Percent Volatiles by Volume:25.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR BASES, OXIDIZING AGENTS AND SELECTED AMINES.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL METHODS MUST COMPLY WITH ALL STATE, LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.