

BAKER SEALANTS AND COATINGS CO, INC. -- PAINT FOR CONCRETE AND MASONARY --
8010-00-584-3362

===== Product Identification =====

Product ID:PAINT FOR CONCRETE AND MASONARY

MSDS Date:11/05/1990

FSC:8010

NIIN:00-584-3362

MSDS Number: BLKYQ

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO, INC.

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone

Num:201-333-6986

Emergency Phone Num:201-333-6986/800-356-3129 CHEMTREC

Preparer's Name:CHARLES FRIEDMAN

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

===== Composition/Information on Ingredients =====

=====

Ingred Name:PETROLEUM SOLVENT
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:300 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 7-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 0.1-0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:
S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:COBALT (SARA III)
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 105F,>41C
Autoignition Temp:Autoignition Temp Text:480 F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON
DIOXIDE. DO NOT USE DIRECT STREAM OF WATER.
Fire Fighting Procedures:PRODUCT WILL FLOAT & CAN BE REIGNITED ON WATER
SURFACE. EVACUATE HAZARD AREA OF UNPROTECTED PERSON

NEL. WEAR PROPER

PROTECTIVE CLOTHING, INCLUDING A NIOSH SCBA.

Unusual Fire/Explosion Hazard:COOL CNTNRS EXPOSED TO INTENSE HEAT FROM FIRES W/WTR/PREVENT VAP PRESS BUILD-UP/POSS RUPTURE. COOL CNTNR AREAS EXPOSED TO DIRECT FLAME CONTACT W/LG AMT WATER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITE SOURCES. WEAR RSPRTR & OTHER PROTECT CLOTH. SHUT OFF SOURCE OF LEAK IF SAFE. DIKE & CONTAIN. REMOVE W/VACUUM TRUCKS OR P

UMP TO STORAGE/SALVAGE VESSLES. SOAK UP

RESIDUE W/ABSORBENT, PLACE IN NONLEAKING CNTNRS, SEAL TIGHTLY FORPROPER **

Neutralizing Agent:**DISPOSAL. FLUSH AREA W/WATER TO REMOVE TRACE RESIDUE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQUID & VAPOR AWAY FROM IGNITE SOURCES. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE OF SPARKS OR FLAME.

Other Precautions:VAPORS MAY ACCUMULATE AND TRAVEL TO IGNITION SOURCES

DISTANT FROM THE HANDLING SITE; FLASH-FIRE CAN RESULT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. CAUTION! COMBUSTIBLE!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH-APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE. IN ACCORD W/29 CFR 1910.134, USE EITHER AN ATMOSPHERE-SUPPLYING OR AN AIR-PURIFYING RSPRTR FOR ORGANIC VAPORS.

Ventilation:USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS WITHIN SUGGESTED PEL/TLV LIMITATIONS.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:OTHER CLOTHING AS REQUIRED TO MINIMIZE.

Supplemental Safety and Health

SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER (800-424-8802). ALSO REPORT

RELEASES TO AIR, LAND OR WATER TO THE NATIONAL RESPONSE CENTER.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315 TO 395F
Vapor Pres:3MM HG@68F
Vapor Density:3.9
Spec Gravity:1.25
pH:6.5
Viscosity:67-82 KU
Evaporation Rate & Reference:2 (BUAC = 1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE, ALIPHATIC ODOR.
Percent Volatiles by Volume:102

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.
Stability Condition to Avoid:AVOID HEAT AND FLAME.
Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF "AS PER LOCAL, STATE OR FEDERAL REGULATIONS." SEAL CONTAINERS, LABEL PROPERLY & DISPATCH TO APPROVED WASTE DISPOSAL FACILITY, ASSURE UNDER EPA-RCRA (40 CFR 261,21) IF THIS PRODUCT BECOMES WASTE MATERIAL, IT WOULD BE HAZARDOUS WASTE HZDS WASTE-D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person

n utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.