

POLYMERIC SYSTEMS, INC. -- PSI 690 PRIMER -- 8040-00-851-0211

=====
Product Identification
=====

Product ID:PSI 690 PRIMER

MSDS Date:03/01/1991

FSC:8040

NIIN:00-851-0211

Kit Part:Y

MSDS Number: BLKZK

=== Responsible Party ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:WHEATLAND & MASON STREETS

City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Info Phone Num:215-935-1170

Emergency Phone Num:215-93

5-1170

Preparer's Name:ED CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 89%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:METHYL ALCOHOL (METHANOL) (SA

RA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL POLYSILICATE
CAS:68412-37-3
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NIF
ACGIH TLV:NIF

Ingred Name:BUTYL POLYTITANATE
CAS:9022-96-2
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NIF
ACGIH TLV:NIF

Ingred Name:VOC: 6.5 LBS/GAL
RTECS #:9999999VO
Other REC Limit
s:NONE SPECIFIED

Ingred Name:VOC: 780 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MUCOUS MEMBRANE IRRITATION,
DROWSINESS, PROSTRATION, NARCOSIS; SKIN IRRITATION; EYE IRRITATION.
CHRONIC: DAMAGE TO LIVER, KIDNEY AND PERIPHERAL & OPTIC NERVE -
JAUNDI

CE, EDEMA AND LOSS OF VISIO N.

Effects of Overexposure:IRRITATION OF MUCOUS MEMBRANES, HEADACHE,
DROWSINESS, FATIGUE, NARCOSIS.

Medical Cond Aggravated by Exposure:EYE, SKIN AND RESPIRATORY DISORDERS
AND IMPAIRED LIVER, KIDNEY AND OPTIC & PERIPHERAL NERVE FUNCTIONS
MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING
IS DIFFICULT. SKIN: FLUSH WIT
H WATER. REMOVE CONTAMINATED CLOTHING.

EYE: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

INGESTION: DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR DROWSY.

OTHERWISE, INDUCE VOMITING. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:56.0F,13.3C

Autoignition Temp:Autoignition Temp Text:793 F

Lower Limits:3.3

Upper Limits:19

Extinguishing Media:DRY CHEMICAL, FOAM, CO2, SAND, WATER SPRAY.

Fire Figh

ting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

OPERATED IN POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:SMOKE MAY CONTAIN HCL AS WELL AS NORMAL
PARTIAL OXIDATION PRODUCTS OF HYDROCARBON COMBUSTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH ABSORBENT MATERIAL. STORE IN
APPROPRIATE CONTAINER. AVOID PROLONGED INHALATION OF VAPOR OR
CONTACT WITH LIQUID. WASH RESIDUES WITH LARGE AMOUNTS OF WATER.

Neutra

lizing Agent:WATER

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID IGNITION SOURCES: FLAME, SPARKS,
EXTREME HEAT. STORE IN WELL VENTILATED AREA.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF LARGE AMOUNTS ARE USED IN A POORLY VENTILATED
CLOSED SPACE, USE A CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC
VAPOR CARTRIDGE(S) (MSHA AN

D NIOSH APPROVED) TO PROTECT AGAINST
ALCOHOL VAPORS.

Ventilation:LOCAL EXHAUST MAY BE REQUIRED IN CLOSED SPACES. RECOMMEND
10 CHANGES PER HOUR.

Protective Gloves:RUBBER OR POLYETHYLENE

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:165F,74C

Melt/Freeze Pt:M.P/F.P Text:-130F,-90C

Decomp Temp:Decomp Text:>752F,>400C

Vapor Pres:42MM @ 68F

Vapor Density:1.8

Spec Gravity:0.80

pH:7

Viscosi

ty:2 CPS @ 20 C

Evaporation Rate & Reference:1.4 VS. BUTYL ACETATE

Solubility in Water:98%

Appearance and Odor:COLORLESS LIQUID, PLEASANT ODOR.

Percent Volatiles by Volume:95

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:OPEN FLAMES, SPARKS, EXTREME HEAT.

Hazardous Decomposition Products:BY COMBUSTION: CO, HCL, AEROSOLS OF
SILICA & TITANIA, INCOMPLETE COMBUSTION PRODUCTS.

=====

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
docume

nt should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.