QCM COMPANY -- P 7002 PLASTISOL VARIOUS COLORS -- 8030-01-041-1609

Product ID:P 7002 PLASTISOL VARIOUS COLORS MSDS Date:11/22/1989 FSC:8030 NIIN:01-041-1609 Kit Part:Y MSDS Number: BLLBR === Responsible Party === Company Name: QCM COMPANY Address:930 SO. CENTRAL AVE. City:KENT State:WA ZIP:98032 Country:US Info Phone Num:206-859-0933 Emergency Phone Num:206-859-0 933 Preparer's Name: ROY WHEELDON CAGE:8L872 === Contractor Identification === Company Name: Q C M CO Address:930 CENTRAL AVE S Box:City:KENT State:WA ZIP:98032-6105 Country:US Phone:253-859-0933, FAX 253-859-0935 CAGE:8L872

Ingred Name:PHTHALATE PLASTICIZER (NOT HAZARDOUS) Other REC Limits:NONE SPECIFIED

Ingred Name: EPOXIDIZED SOYBEAN OIL (NOT HAZARDOUS) Other REC Limits: NONE SPECIFIED

Ingred Name: PVC RESIN (NOT HAZARDOUS) O

ther REC Limits:NONE SPECIFIED
Ingred Name:STABILIZER (NOT HAZARDOUS) Other REC Limits:NONE SPECIFIED
Ingred Name:ORGANIC PIGMENT (NOT HAZARDOUS) Other REC Limits:NONE SPECIFIED
Ingred Name:CADMIUM CARBOXYLATE STABILIZER Fraction by Wt: 0.1% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 MG/M3 (CADMIUM)
Ingred Name:ORGANIC PIGMENT (NOT HAZARDOUS) Other REC Limits:NONE RECOMMENDED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EYE: MAY CAUSE IRRITATION. SKIN: CAN CAUSE SLIGHT IRRITATION. INHALATION: SMOKE SHOULD BE VENTILATED IF HEAT PROCESSED. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.
======================================
First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. EXCESSIVE INHALATION, REMOVE TO FRESH AIR. INGESTION: CONSULT PHYSICIAN.
====== ===============================
Flash Point:>350F,>177C Extinguishing Media:DRY CHEMICAL, REGULAR FOAM OR WATER FOG. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS IF IGNITED.
Unusual Fire/Explosion Hazard:TOXIC GASES CAN FORM-CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS.
======================================

Spill Release Procedures:SMALL SPILLS: ABSORB ON VERMICULITE OR FLOOR DRY. LARGE SPILL

## S: PUMP TO SALVAGE TANK.

OBSERVED.

Handling and Storage Precautions:CONTAINERS MAY BE HAZARDOUS WHEN EMPTIED DUE TO VAPOR BUILD-UP. STORE BETWEEN 50 F AND 90 F, AWAY FROM HEAT OR FLAME. Other Precautions:ALL HAZARD PRECAUTIONS IN THE DATA SHEET MUST BE

Respiratory Protection:RECOMMENDED IF LOCAL EXHAUST. NIOSH APPROVED. Ventilation:LOCAL EXHAUST: RECOMMENDED FOR HEAT PROCESSING. MECHANICAL (GENERAL): RECOMMENDED. Protective Gloves:POLYETHYLENE TYPE Eye Protection:SAFETY GLASSES Work Hygienic Practices:GOOD INDUSTRIAL HYGIENE. WASH WITH SOAP AND WATER IF CONTACT W/SKIN. WASH CONTAMINATED CLOTHING BEFORE RE-USE. Supplemental Safety and Health

Spec Gravity:1.1 Solubility in Water:NEGLIGIBLE Appearance and Odor:VARIOUS COLORED LIQUID-VISCOUS

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURES. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, VARIOUS HYDROCARBONS, HYDROGEN CHLORIDE.

Waste Disposal Methods: INCINERATE ACCORDING TO LOCAL AND FEDERAL STANDARDS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.