

E/M CORPORATION -- ESNALUBE 382 -- 9150-01-328-2552

=====
Product Identification
=====

Product ID:ESNALUBE 382

MSDS Date:08/18/1989

FSC:9150

NIIN:01-328-2552

MSDS Number: BLPRV

=== Responsible Party ===

Company Name:E/M CORPORATION

Address:6940 FARMDALE AVE

City:NORTH HOLLYWOOD

State:CA

ZIP:91605-6210

Info Phone Num:(213) 875-0101

Emergency Phone Num:(213) 875-0101

CAGE:EMCOR

=== Contractor Ident

ification ===

Company Name:E/M CORP

Address:6940 FARMDALE AVE

City:NORTH HOLLYWOOD

State:CA

ZIP:91605-6210

Country:US

Phone:317-497-6100

CAGE:11770

Company Name:E/M CORPORATION

Address:2601 KENT AVE

Box:2400

City:WEST LAFAYETTE

State:IN

ZIP:47906

Phone:(317) 497-6100

CAGE:EMCOR

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

OSHA PEL:15 MG/CUM AS (MO)

ACGIH TLV:10 MG/CUM AS (MO)

Ingred Name:WETTING AGENT

In

Product Name: INORGANIC SILICATE BINDER

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture: ORAL (RAT) LD50: 1,280 MG/KG. SEE SUPP.

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYES: IRRITATION, REDNESS, BLURRED VISION. SKIN: IRRITATION, DERMATITIS. INHALATION: IRRITATION, DIZZINESS, NAUSEA, FATIGUE, HEADACHE, UNCONSCIOUSNESS OR ASPHYXIATION. INGESTION:

GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: EYES: IRRITATION, REDNESS, BLURRED VISION. SKIN: IRRITATION, DERMATITIS. INHALATION: IRRITATION, DIZZINESS, NAUSEA, FATIGUE, HEADACHE, UNCONSCIOUSNESS OR ASPHYXIATION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA.

=====
===== First Aid Measures =====
=====

First Aid: SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/COPIOUS AMOUNTS OF

WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. KEEP WARM. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====
=====

Extinguishing Media: CO2, FOAM, DRY CHEMICAL, OR HALON

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures: CLEAN SPILL W/ABSORBENT MATERIAL. FLUSH W/LARGE QUANTITIES OF WATER INTO INDUSTRIAL SEWER.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions: PROTECT FROM PHYSICAL DAMAGE. STORE IN A COOL, DRY, VENTILATED AREA AWAY FROM ACIDS, ALKALIS & OPEN FLAMES.

Other Precautions: AVOID CONTACT W/SKIN.

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection: USE NIOSH APPROVED ORGANIC RESPIRATOR IF >TLV.

Ventilation: LOCAL EXHAUST: TO KEEP