View NSN Online: https://aerobasegroup.com/nsn/9150-01-109-7793

Product ID:R-258 SPECIAL LUBRICANT (MIL-L-46150) MSDS Date:01/03/1995 FSC:9150 NIIN:01-109-7793 MSDS Number: BLSSZ === Responsible Party === Company Name: ROY DEAN PRODUCTS CO Address:45800 MAST STREET City:PLYMOUTH State:MI ZIP:48170-6056 Country:US Info Phone Num:313-451-2800 Emer gency Phone Num:313-451-2800 Preparer's Name: JAMES F. WIRTZ CAGE:0DRK3 === Contractor Identification === Company Name: ROY DEAN PRODUCTS CO Address:45800 MAST STREET Box:City:PLYMOUTH State:MI ZIP:48170-6007 Country:US Phone:313-451-2800 CAGE:0DRK3 Ingred Name:"NOT HAZARDOUS" Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:TLV FOR OIL

MIST IS 5 MG/M3. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN, RESPIRATORY TRACT. ACUTE- MAY CAUSE EYES & SKIN IRRITATION. PROLONGED/REPEATED SKIN CONTACT CAUSES DEFATTING. INHALATION OF VAPORS/OIL MIST MAY CAUSE IRRITATION. INGESTION MAY CAUSE NAUSEA. ASPIRATION HAZARD. CHRONIC- UNKNOWN. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, NAUSEA Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT. First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN: WIPE OFF EXCESS. WASH SKIN WITH SOAP & WA TER. ORAL: DO NOT INDUCE VOMITING. IF CONSCIOUS, RINSE MOUT H. SEEK MEDICAL ATTENTION. DO NOT DRINK. IF SPONTANEOUS VOMITING OCCURS, MONITOR FOR BREATHING DIFFICULTY. Flash Point Method:COC Flash Point:500F,260C Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM/DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. **Unusual Fire/Explosion Hazar** d:CONTAINER MAY BURST.

Spill Release Procedures: VENTILATE AREA. RECOVER FREE OIL IF POSSIBLE. ABSORB SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH & SHOVELD INTO CONTAINERS FOR LATER DISPOSAL. PREVENT RUN-OFF TO ENTER WATERWAYS, SEWERS. ALL R ESPONSE ACTIVITIES MUST COMPLY WITH HAZWOPER.

Neutralizing Agent:NOT RELEVANT

Handling and Stor

age Precautions:STORE AWAY FROM HEAT, FLAME & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDER BEFORE RE-USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. IF EXPOSURE MAY O R DOES

EXCEED OCCUPATIONAL EXPOSURE LIMITS, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation: USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE OR NEOPRENE RECOMMENDED

Eye Protection: SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

HCC:V6 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:600F,316C Spec Gravity:0.96 - 0.99 Evaporation Rate & amp; Reference: