View NSN Online: https://aerobasegroup.com/nsn/8010-01-285-3033

DEFT INC CHEMICAL COATING DIV -- CAT,MIL-C-85285B, 17038, TYPE I, 03BK071CAT 8010-01-285-3033

Product ID:CAT,MIL-C-85285B, 17038, TYPE I, 03BK071CAT

MSDS Date:07/31/1991

FSC:8010

NIIN:01-285-3033

Kit Part:Y

MSDS Number: BLSVF === Responsible Party ===

Company Name: DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Coun

try:US

Info Phone Num:949-474-9499

Emergency Phone Num:949-474-9499

Preparer's Name: NORM GAUL

CAGE:KO194

=== Contractor Identification ===

Company Name: DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Country:US

Phone:949-474-9499

CAGE:KO194

Company Name: DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Country:US

Phone:949-474-0400

CAGE:33461

====== Composition/Information on Ingredients ========

Ingred Name:TOLUENE

(SARA III) CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 15%

Other REC Limits: NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ALIPHATIC ISOCYANATE (VAPOR PRESSURE 0 MM HG)*

CAS:28182-81-2 Fraction by Wt: 50%

Other REC Limits: MOBAY TLV: 1 MG/M3

Ingred Name:*HEXAMETHYLENE DIISOCYANATE (HDI) CAS NO 822-06-0, FREE MONOMER CONTENT LESS THAN 0.7% BASED ON RESIN SOLIDS AT TIME**

RTECS #:9999999ZZ

Other REC Limits: NONE SPECIF

IED

Ingred Name:**OF MFR. AFTER 3-6 MO STORAGE FREE MONOMER CONTENT MAY RISE (MAX 1.6%). THE ACGIH HAS PROPOSED A TLV OF 0.005 PPM ***

RTECS #:9999999ZZ

Other REC Limits: NONE SPECIFIED

Ingred Name:***TWA IN THE NOTICE OF INTENDED CHANGES FOR 1987-88. MOBAY RECOMMENDS A CEILING LEVEL OF 0.02 PPM.

RTECS #:9999999ZZ

Other REC Limits: NONE SPECIFIED

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 40%

Other REC Limits: NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: VOC: 485 G/L

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

============= Hazards Identification ==================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE: VAPORS IRRITATING TO

EYES/NOSE/THROAT. INHALATION: IRRITATION, ACUTE NERVOUS SYSTEM

DEPRESSION. CHRONIC: PROLO

- NGED CONTACT WILL CAUSE DEFATTING ACTION.
 INGESTION: IRRITATION. ASPIRATION CAN CAU SE CHEMICAL PNEUMONITIS.
 AS A RESULT OFPREVIOUS REPEATED OVEREXPOSURE OR SINGLE LARGE DOSE,
 CERTAIN INDIVIDUALS WILL**
- Effects of Overexposure:INHAL: DIFFICULT BREATHING, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS, COMA. SKIN: IRRIT (SWELLING/REDNESS/RASH). EYES: REDNESS, TEARING, SWELLING W/STINGING. SKIN: SWELL/REDNES S/RASH. PROLONG/REPEAT--MOD IRRIT, DRYING, S
- KIN CRACKING. INGEST: VOMIT. IRRIT. CORROSIVE TO MOUTH/STOMACH/DIGEST TRACT.
- Medical Cond Aggravated by Exposure: ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS.

- First Aid:INHALATION: MOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS MAY DEVELOP (IMMED/DELAYED BY SEVERAL HRS). GET MED AID. SKIN: REMOVE CONTAM CLOTHING. WASH AREA W/SOAP & WATER. WASH CONTAM C L
- OTHING BEFORE REUSE. EYES: FLUSH WITH LUKEWARM WATER (LOW PRESSURE)--15 MIN, LIFTING UPPER/LOWER LIDS. GET MED AID. INGESTION: DON'T INDUCE VOMIT. NOTHING BY MOUTH TO UNCONSCIOUS PERSON. GET MED AID.

Flash Point Method:TCC Flash Point:45.0F,7.2C

Lower Limits:1%


Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures:FULL FIRE FIGHT EQUIP W/SCBA & FULL PROTECT CLOTH. USE W

ATER TO COOL CLOSED CNTNRS/PREVENT PRESSURE BUILD-UP/AUTO IGNITE/EXPLOSION. HDI/IRRIT VAPORS GENERATED.

Unusual Fire/Explosion Hazard:KEEP FROM IGNITE SOURCES. CLOSED CNTNR MAY EXPLODE W/HEAT. USE SPECIAL PRECAUTION W/APPLIC TO HOT SRFCS. DURING EMERG COND, OVEREXPOS TO DECOMP PROD/HEALTH HZD.

======== Accidental Release Measures ===========

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HO



Boiling Pt:B.P. Text:231 TO 237F

Vapor Density:> AIR

Spec Gravity:0.94

Viscosity:*

Evaporation Rate & Dr. Reference: 1.39 X N-BUTYL ACETATE

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER LIQUID WITH SOLVENT ODOR.

Percent Volatiles by Volume:59.5

======	Stability and Reactivity Data	=======================================
--------	-------------------------------	---

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIALS WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

===	 Disposal	Considerati
ons	 ===	

Waste Disposal Methods:WASTE MUST BE DISPOSED IN ACCORD W/FEDERAL, STATE & LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED W/CARE (PRODUCT RESIDUE/FLAMMABLE VAPOR). DON'T INCINERATE CLOSED CNTNRS. EPA HAZARDOUS WASTE #: D001, F003, F005.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no mann er whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.