View NSN Online: https://aerobasegroup.com/nsn/8010-00-901-8048

DAVLIN PAINT CO -- B509TB ALKYD SG ODORLESS GREEN 24672 -- 8010-00-901-8048

Product ID:B509TB ALKYD SG ODORLESS GREEN 24672 MSDS Date:02/25/1991 FSC:8010 NIIN:00-901-8048 MSDS Number: BLVBG === Responsible Party === Company Name: DAVLIN PAINT CO Box:2308 City:BERKELEY State:CA ZIP:94702 Country:US Info Phone Num:510-848-2863 Emergency Phone Num:800-424-9300 (CHEM TREC) Preparer's Name: PATRICIA SHAW CAGE:3Z268 === Contractor Identification === Company Name: DAVLIN PAINT CO INC Address:700 ALLSTON WAY Box:2308 City:BERKELEY State:CA ZIP:94702 Country:US Phone:510-848-2863 CAGE:3Z268

Ingred Name:HYDROCARBON MIXTURE (VAPOR PRESSURE 2.0 MM HG @ 68F) CAS:64741-41-9 Fraction by Wt: 20% Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:100 PPM

Ingred Name:SILICA, QUARTZ CAS:14808-60-

7 RTECS #:VV7330000 Fraction by Wt: 0.26% Other REC Limits:NONE SPECIFIED OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:PETROLEUM HYDROCARBON (VAPOR PRESSURE 50.0 HG MM @ 0 F) CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 5% Other REC Limits:100 PPM OSHA PEL:500 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chr

onic:INHALATION: RESPIRATORY IRRIT, CENTRAL

NERVOUS SYS DEPRESSION. SKIN/EYE: PROLONG/REPEAT EXPOSURE--MODERATE IRRIT, DEFATTING & DERMATITIS. INGEST: DIGESTIVE TRACT IRRIT, LUNG INFLAMMATION. CAUSES DAMAG ES TO CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, GASTROINTESTINAL TRACT, LIVER, SPLEEN AND KIDNEYS.

Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED (IARC) CARCINOGEN. ACGIH ASSIGNED TLV'S TO MATERIAL. SEE INGREDS FOR TLV. Effects of Overe

xposure:INHALATION: NASAL/RESPIRATORY IRRITATION,

DIZZINESS, WEAKNESS, FATIGUE, NAUSEA AND HEADACHE. EYE: IRRITATION, TEARING, REDNESS, & BLURRED VISION. SKIN: MODERATE IRRITATION. INGESTION: ASPIRATION HAZAR D; THIS MATERIAL CAN ENTER THE LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION. Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

First Aid:EYE: FLU

SH W/WATER--15 MIN, OCCASIONALLY LIFTING EYELIDS.

OBTAIN MED ATTN. SKIN: REMOVE CONTAM CLOTHING. WASH W/SOAP & WATER. IF IRRIT PERSISTS, SEE DOCTOR. INHAL: REMOVE TO FRESH AIR. APPLY ARTIFICIA L RESP OR ADMIN OXYGEN. CONSULT A DR. INGEST: GIVE WATER/MILK TO DRINK & PHONE FOR MEDICAL ADVICE. DON'T INDUCE VOMIT UNLESS MEDICAL PERSONNEL ADVISES. MED ADVICE UNAVAILABLE, TAKE TO EMERG HOSPITAL.

Flash Point

Method:SCC Flash Point:104F,40C Lower Limits:0.7% Upper Limits: 6.1% Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures: USE EXTINGUISHERS (NFPA FLAMMABLE LIQUID FIRE). WATER MAY BE INEFFECTIVE, USE AS FOG FOR COOLING. WEAR FULL PROTECT CLOTH/BREATH APP IF EXPOS TO COMBUST PROD. Unusual Fire/Explosion Hazard: VAPORS FORM EXPLOSIVE MIX WHICH CAN BE IGNITED FROM MANY SOURCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. ISOLAT E FORM IGNITION SOURCES. Spill Release Procedures: EVACUATE NON-ESSENTIAL PERSONEL. REMOVE ALL IGNITION SOURCES. VENTILATE THE AREA. PROVIDE APPROPRIATE PROTECTIVE EQUIPMENT. DIKE AROUND THE SPILL AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER US ING NON-SPARKING TOOLS. Handling and Storage Precautions: STORE BELOW 80 F IN A CLOSED CONTAIN ER. STORE IN ORIGINAL CONAINER. AVOID FLAME & HIGH TEMPERATURES. DON'T STORE NEAR OXIDIZING AGENTS OR ACIDS. Other Precautions: VAPOR HEAVIER THAN AIR & MAY TRAVEL DISTANCE TO IGNIT SOURCES & FLASHBACK. DON'T EAT. NO PROLONG/REPEAT INHAL OF HEATED VAPORS/ SPRAY MISTS, KEEP FROM HEAT, GROUND ALL CONNECTIONS. CNTNRS, ETC (POURIN G/ TRANSFERING). USE NON-SPARKING TOOLS. Respiratory Protection: USE NIOSH/MSHA APPROVE D EQUIPMENT WHEN AIRBORN EXPOSURE LIMITS ARE EXCEEDED. CONSULT RESPIRATOR MFR TO DETERMINE APPROPRIATE EQUIPMENT FOR GIVEN APPLICATION. HIGH AIRBORN CONCENTRATIONS MAY REQUIRE THE USE OF A SUPPLIED-AIR **RESPIRATOR/SCBA**.

Ventilation: PROVIDE SUFFICIENT VENTILATION TO CONTROL EXPOSURE LEVELS BELOW AIRBORN TLVS. VENT EQUIPMENT MUST BE EXPLOSION PROOF. Protective Gloves: CONSULT GLOVE MFR FOR APPROPRIATE TYPE Eye Protection: CHEM SFTY GLASSES/GOGGLES(SPLASH SHIELD) Other Protective Equipment:WEAR IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR EXTENDED EXPOSURE OF SKIN.

Work Hygienic Practices: AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR REPRODUCTIVE HARM. THE USE OF HEAD CAPS WHENEVER POSSIBLE IS STRONGLY RECOMMENDED.

HCC:F

4 Boiling Pt:B.P. Text:315 TO 335F Vapor Density:> AIR Spec Gravity:1.4 (WATER=1) Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:NOT SOLUBLE Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON

DIOXIDE AND/OR MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

Waste Disposal Methods: KEEP OUT OF DRAINS, SEWERS, AND WATERWAYS. DISPOSE OF PRODUCT IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manne

r whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.