View NSN Online: https://aerobasegroup.com/nsn/3439-00-178-8590

CYC HOLDINGS INC DBA HI-TECH ALLOYS -- ALUMINUM WELDING WIRE -- 3439-00-178-8590

Product ID:ALUMINUM WELDING WIRE

MSDS Date:01/01/1987

FSC:3439

NIIN:00-178-8590

MSDS Number: BLVZW === Responsible Party ===

Company Name: CYC HOLDINGS INC DBA HI-TECH ALLOYS

Address:25 WEST ST

Box:536

City:STAFFORD SPRINGS

State:CT ZIP:06076 Country:US

Info Phone Num:800-448-3229

Em

ergency Phone Num:203-684-6326

CAGE:0B491

=== Contractor Identification ===

Company Name: CYC HOLDINGS INC DBA HI-TECH ALLOYS

Address:25 WEST ST

Box:536

City:STAFFORD SPRINGS

State:CT ZIP:06076 Country:US

Phone:203-684-6326

CAGE:0B491

======= Composition/Information on Ingredients ========

Ingred Name: ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000 Fraction by Wt: 94-95.5%

Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:SI

| CAS:7440-21-3 RTECS #:VW0400000 Fraction by Wt: 4.5-6.0% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293 |
|--|
| ====================================== |
| LD50 LC50 Mixture:TLV FOR WELDING FUMES IS 5 MG/M3 Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: FUMES AND GASES CAN CAUSE EYES AND UPPER RESPIRATORY SYSTEM IRRITATION. ARC RAYS CAN INJURE EYES |
| AND BURN SKIN. ELECTRIC SHOCK CAN KILL. NOISE CAN DAMAGE HEARING. CHRONIC: LUNG FIBROSIS, PNEUMO CONIOSIS. Effects of Overexposure:SHORT TERM EXPOSURE: NAUSEA, FEVER, DIZZINESS, DRYNESS, IRRITATION OF EYES, NOSE AND THROAT, SKIN SENSITIVITY. ACUTE EXPOSURE: SAME SYMPTOMS TO HIGHER DEGREE AS WELL AS WATERY EYES, HEADACHE, BREATHIN G DIFFICULTY, FREQUENT COUGHING, CHEST PAINS. |
| Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY |
| O R ALLERGIC CONDITIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG SMOKERS. |
| ====================================== |
| First Aid:INHALATION: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF NOT BREATHING, GIVE CPR. IF NO DETECTABLE PULSE, GIVE HEART MASSAGE. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 1 5 MINUTES. SKIN: WASH WITH SOAP AND WATER. |
| ====================================== |
| Extinguishin g Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. |
| |

======== Accidental Release Measures ===========

Spill Release Procedures: COLLECT SCRAP FOR REMELTING. C

| GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPIATE DISPOSAL CONTAINER. AVOID INHALATION AND SKIN EXPOSURE. |
|---|
| ====================================== |
| Handling and Storage Precautions:STORE IN DRY AREA. Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA. |
| ====== Exposure Controls/Personal Protection ======== |
| Respir atory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV. Protective Gloves:WELDER'S GLOVES. Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS. Other Protective Equipment:SUBSTANTIAL DARK CLOTH, ARM PROTECTOR, APRON, HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE MEASURES Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING, SMOKIN G OR USING SANITARY FACILITIES. Supplemental Safety and Health ALUMINUM IS WELDED IN A PROTECTIVE, INERT ATMOSPHERE SUCH AS ARGON OR HELIUM USING THE MIG OR TIG PROCESS. |
| ========= Physical/Chemical Properties ========== |
| HCC:N1 Melt/Freeze Pt:M.P/F.P Text:>970F,>521C Spec Gravity:2.8 Solubility in Water:INSOLUBLE Appearance and Odor:SOLID, STRAIGHT LENGTH WELDING ROD. 0.062 INCHES DIAMETER BY 36 INCHES LONG. |
| ======== Stability and Reactivity Data ===== |

========

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:FUMES OF METALS AND METAL OXIDES FROM ELECTRODE AND BASE METAL, CARBON MONOXIDE, CARBON DIOXIDE, OZONE, NITROGEN OXIDES.

======= Disposal Considerations ==========

Waste Disposal Methods:WASTE THAT CANNOT BE REUSED OR RECYCLED MAY BE DISPOSED OF IN A SANITARY LANDFILL. COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their par

ticular situation.