

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- BEACON 325 -- 9150-00-911-7823

=====
Product Identification
=====

Product ID:BEACON 325

MSDS Date:07/01/1985

FSC:9150

NIIN:00-911-7823

MSDS Number: BLWGL

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-656-5949 FAX: 713-656-36

31

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

Company Name:TELEMECHANICS INC

Address:1636 FIFTH AVE

Box:City:BAY SHORE

State:NY

ZIP:11

706
Country:US
Phone:516-231-3833
CAGE:57712

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. INGESTION:
THIS PRODUCT HAS A LOW DEGREE OF TOXICITY, BUT MINUTE AMOUNTS
ASPIRA
TD INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE MILD
TO SEVERE PULMONARY INJURY. PR OLONGED OR REPEATED SKIN CONTACT
MAY CAUSE SKIN IRRITATION.
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT WITH THIS
PRODUCT TENDS TO REMOVE SKIN OILS POSSIBLY LEADING TO IRRITATION
AND DERMATITIS.
Medical Cond Aggravated by Exposure:NONE RECOGNIZED

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTI
L IRRITATION
SUBSIDES. SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN
THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE
AND CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL A
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:415F,213C
Autoignition Temp:Autoignition Temp Text:>260C
Lower Limits:1.0
Upper Limits:12.0
Extinguishing Media:FOAM, WATER SPRAY (FOG), DRY CHEMICAL, CARBON

DIOXIDE AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.

Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS. USE SUPPLIED-AIR BREATHING EQUIPMENT

Unusual Fire/Explosion Hazard:THIS MATERIAL WILL EMIT TOXIC DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA.

Other Precautions:NONE 30JAN92CD
68500130464160BYN5A

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:500F,260C

Vapor Pres:5

Spec Gravity:0.94

Viscosity:280 ASTM D217

Evaporation Rate & Reference: