

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- 1209 TURBINE LUBRICANT -- 9150-01-263-7242
===== Product Identification =====

Product ID:1209 TURBINE LUBRICANT

MSDS Date:08/10/1987

FSC:9150

NIIN:01-263-7242

MSDS Number: BLWHM

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-6

56-5949 FAX: 713-656-3631

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:EXXON COMPANY U.S.A.

Address:Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Bo

x:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Phone:713-656-5949 FAX: 713-656-3631
CAGE:DO850

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. INGESTION:
THIS PRODUCT
HAS A LOW DEGREE OF TOXICITY, BUT MINUTE AMOUNTS
ASPIRATED INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE MILD
TO SEVERE PULMONARY INJURY. PROLONGED OR REPEATED SKIN CONTACT
MAY CAUSE SKIN IRRITATION.
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT WITH THIS
PRODUCT TENDS TO REMOVE SKIN OILS POSSIBLY LEADING TO IRRITATION
AND DERMATITIS.
Medical Cond Aggravated by Exposure:NONE RECOGNIZED

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION
SUBSIDES. SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN
THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE
AND CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL A
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:399F,204C
Autoignition Temp:Autoignition Temp Text:>260C
Lower Limits:0.9
Upper Limits:7.0
Extinguis

hing Media:FOAM, WATER SPRAY (FOG), DRY CHEMICAL, CARBON DIOXIDE AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.
Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS. USE SUPPLIED-AIR BREATHING EQUIPMENT
Unusual Fire/Explosion Hazard:THIS MATERIAL WILL EMIT TOXIC DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES, IF NEEDED.
Ventilation:USE LOCAL EXHAUST TO CAPTURE VAPOR, MISTS OR FUMES, IF NECESSARY. USE EXPLOSION-PROOF EQUIPMENT.
Protective Gloves:USE CHEMICAL-RESISTANT GLOVES.
Eye Protection:USE SPLASH GOGGLES OR FACE SHIELD.
Other Protective Equipment:USE CHEMICAL-RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING
Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:556F,291C
Vapor Pres:5
Spec Gravity:0.88
Viscosity:77 CST
Evaporation Rate & Reference: