View NSN Online: https://aerobasegroup.com/nsn/3439-00-702-4067

GARDINER SOLDER CO. -- TIN, LEAD, ANTIMONY SOLDER, X-45, CODE 185 -- 3439-00-702-4067

Product ID:TIN, LEAD, ANTIMONY SOLDER, X-45, CODE 185

MSDS Date:02/13/1987

FSC:3439

NIIN:00-702-4067

MSDS Number: BLXHB === Responsible Party ===

Company Name: GARDINER SOLDER CO.

Address:4820 SO. CAMPBELL AVE

City:CHICAGO

State:IL ZIP:60632

Info Phone Num:312-847-0100

Emergency Phone N um:312-847-0100

CAGE:56244

=== Contractor Identification ===

Company Name: GARDINER SOLDER CO, DIV OF GARDINER METAL CO

Address:4820 S CAMPBELL AVE

Box:City:CHICAGO

State:IL

ZIP:60632-1416 Country:US

Phone:312-847-0100/800-424-9300(CHEMTREC)

CAGE:56244

====== Composition/Information on Ingredients ========

Ingred Name:TIN CAS:7440-31-5

RTECS #:XP7320000 Fraction by Wt: 63.5% OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 8990

Ingred Name: ANTIMONY (METAL)

CAS:7440-36-0

RTECS #:CC4025000

Frac

tion by Wt: 0.5%
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG/M3; 8990
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 35.53%
Other REC Limits:0.05MG/FT*3
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3; 8990

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ROSIN CAS:8050-09-7

=========== Hazards Identification ==========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and

Chronic:EYES:I

RRITATION,BURNS;SKIN:BURNS;INHALATION; IRRITATION OF MUCOUS MEMBRANES,SWEETISH METALLIC TASTE,BURNING IN MOUTH; INGESTION:N/R. CHRONIC HAZARD:ANOREXIA "LEAD LINE" ON GUM MARGIN,NAUSEA, SEVERE AB DOMINAL PAIN,VISUAL DISTURBANCE,PARALYSIS.

Effects of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:PULMONARY INSUFFICIENCIES & PRE-EXISTING EYE DISORDERS.

First Aid:EYES:WASH WITH LARGE AMOUNTS
OF WATER & APPLY SOOTHING
SOLUTION;SKIN:APPLY BURN OINTMENT;INHALATION:REMOVE TO FRESH AIR.
IF DISCOMFORT PERSISTS,SEE DOCTOR.

========== Fire Fighting Measures ==============

Extinguishing Media:ANY MEDIA APPROPRIATE FOR SURROUNDING FIRE.AVOID USING WATER ON MOLTEN ALLOY.IT GENERATES MUCH STEAM WITH METAL SPLASHNG

Fire Fighting Procedures:IN HIGH TEMPERATURE FIRE,>1832F(>1000C),WEAR SCBA FOR PROTECTION AGAINST LEAD FUMES.

Unusual Fire/Explosion Hazard:W

ELDING ARCS & SPARKS CAN IGNITE COMBUSTIBLE PRODUCTS.
======== Accidental Release Measures =========
Spill Release Procedures:FINE DUST SHOULD BE VACUUMED.
========== Handling and Storage ============
Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOCK BY MAINTAING DRY WORK AREA.
====== Exposure Controls/Personal Protection ========
Respirato ry Protection:NIOSH/MSHA APPROVED FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation:LOCAL EXHAUST TO MAINTAIN BELOW TLV. Protective Gloves:FINE DISPOSABLE GLOVES DURING SOLDERING. Eye Protection:SAFETY GLASSES/GOGGLES DURING SOLDERING. Other Protective Equipment:CLOTHING APPROPRIATE FOR SOLDERING-EYE BATH STATION NEAR SOLDERING. Work Hygienic Practices:IF HANDLED WITH BARE HANDS,WASH THOROUGHLY AFTER H ANDLING. Supplemental Safety and Health
Supplemental Safety and Health SPECIFIC GRAVITY,FLUX:1.0;ALLOY:8.55-MELTING POINT,FLUX:180F(82C);ALLOY:361F(182C)-SCREEN EMPLOYEES FOR PRE-EXISTING SKIN DISORDERS,PULMONARY INSUFFICIENCIES,LIVER & KIDNEY FUNCTIONS.DO NOT ALLOW PREG NANT WOMEN IN SOLDERING AREA.
======================================
HCC:N1 Melt/Freeze Pt·M P/F P Text·SFF SUPPI

Melt/Freeze Pt:M.P/F.P Text:SEE SUPPL Spec Gravity:SEE SUPPL DATA Solubility in Water:INSOLUBLE Appearance and Odor:FLUX:AMBER SOLID,NO ODO

Percent Volatiles by Volume:NONE
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Hazardous Decomposition Products:FUMES & PARTICULATES OF METALS & META OXIDES,CO,CO*2,OXIDES OF NITROGEN,VARIOUS HYDROCARBONS,O*3.
======== Disposal Considerations ===========

Waste Disposal Methods:RECYCLING. DISPOSE OF RESIDUE FROM WORK AREA OR FILTERS IAW FEDER AL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informati on to their particular situation.

R.ALLOY:SILVER GREY SOLID.NO