

M AND T CHEMICALS INC FURANE PRODUCTS DIVISION -- ARALDITE HARDENER HY 956, KIT P/N TL 5493 -- 2010-01-252-8348

===== Product Identification =====

Product ID:ARALDITE HARDENER HY 956, KIT P/N TL 5493

MSDS Date:03/01/1983

FSC:2010

NIIN:01-252-8348

Kit Part:Y

MSDS Number: BLZHW

=== Responsible Party ===

Company Name:M AND T CHEMICALS INC FURANE PRODUCTS DIVISION

Address:5121 SAN FERNANDO RD W

City:

LOS ANGELES

State:CA

ZIP:90039-1011

Country:US

Info Phone Num:818-247-6210

Emergency Phone Num:818-247-6210

CAGE:76323

=== Contractor Identification ===

Company Name:CIBA SPECIALTY CHEMICALS CORP, N. A. / PERFORMANCE
POLYMERS

Address:5121 SAN FERNANDO RD WEST

Box:City:LOS ANGELES

State:CA

ZIP:90039-1011

Country:US

Phone:818-247-6210/800-873-1138

CAGE:99384

Company Name:M AND T CHEMICALS INC SUB OF AMERICAN CAN CO

Box:1104

City:RAHWAY

State:NJ

ZIP:07065-1104

Country:US

CAGE:76323

=====

== Composition/Information on Ingredients =====

Ingred Name:HYDROXYALKYLATED POLYAMINE

Fraction by Wt: 100% %

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL (RAT) 4500 MG/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN IRRITANT, EYE IRRITANT

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:SKIN IRRITATION, SEVERE EYE IRRITATION

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN: IMMEDIATELY REMOVE LIQUIDS FROM THE SKIN BY WIPING WITH DISPOSABLE TOWEL; THEN WASH AFFECTED AREA THOROUGHLY WITH WARM SOAPY WATER. ANY MATERIAL STILL ADHERING SHOULD BE REMOVED WITH RESIN-REMOVING CREAM. D

DO NOT USE SOLVENTS. EYES: FLUSH WITH WATER

FOR 15 MINUTES. INHALATION: REMOVE TO FRESH AIR. INGESTION:

IMMEDIATELY RINSE MOUTH. IF SWALLOWED, DRINK LOTS OF WATER. CONTACT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:302F,150C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:WATERSPRAY OR FOAM OR CARBON DIOXIDE OR DRY POWDER OR VAPORISING LIQUID

Fire Fighting Procedures:DO NOT USE WATER JETS.

IN A SERIOUS FIRE IT

MAY BE NECESSARY TO WEAR A COMPRESSED AIR BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:AVOID PRODUCTS OF COMBUSTION WHILE PUTTING OUT THE FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH AFFECTED AREA THOROUGHLY WITH WATER.

CLEAN UP WITH ABSORBENT MATERIAL (SAND, SAWDUST, COTTON WASTE, PAPER TOWELS, ETC.). REMOVE CONTAMINATED ABSORBENT TO A SAFE PLACE PENDING DISPOSAL. THEN WASH AREA WITH D

ETERGENT SOLUTION,
PREFERABLY HOT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS SECURELY IN A COOL,
DRY PLACE. STORE AWAY FROM FOOD AND FOOD CONTAINERS.

Other Precautions:WHENEVER THE FULLY CURED OR HARDENED MATERIALS IS TO
BE MACHINED, THE EQUIPMENT SHOULD BE PROVIDED WITH AN EFFECTIVE
LOCAL EXTRACTION SYSTEM. OPERATORS SHOULD WEAR EYE PROTECTION AND A
DUST MASK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED

Ventilation:GOOD GENERAL (MECHANICAL) VENTILATION SHOULD BE SUFFICIENT.
MIXING SHOULD TAKE PALCE IN A VENTILATED HOOD.

Protective Gloves:NITRILE, NATURAL RUBBER, POLYETHYLENE

Eye Protection:SAFETY GLASSES, GOGGLES

Other Protective Equipment:OVERALLS AND HEAVY-DUTY APRONS, EMERGENCY
EYEWASH AND SHOWER

Work Hygienic Practices:SKIN SHOULD BE THOROUGHLY CLEANSED AS

A

STANDARD ROUTINE AFTER WORK AND BEFORE EATING, DRINKING, SMOKING.

Supplemental Safety and Health

WHEN WORK IS TO BE CARRIED OUT IN A TANK OR SIMILAR CONFINED SPACE, A
PERMIT-TO-WORK SYSTEM SHOULD BE IMPLEMENTED. THE SYSTEM SHOULD
INCLUDE BREATHING APPARATUS, A SAFETY HARNESS AND LINE, AND A SECON
D MAN IN ATTENDANCE WITH RESERVE BREATHING APPARATUS.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.

P Text:NOT GIVEN

Vapor Pres:0.1 PA@20C

Vapor Density:1.01 @20C

Spec Gravity:NOT GIVEN

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID, AMINE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

EPOXY RESINS

Stability Condition to Avoid:EXTREME TEMPERATURES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.
OXIDES OF NITROGEN

Conditions to Avoid Polymerization:AVO

ID CONTACT WITH EXPOXY RESINS
UNTIL READY FOR USE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accu
rate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.