

MAGRUDER COLOR CO. INC. -- NON REMOVABLE AIRCRAFT FINISH -- 8010-00-181-7859

=====  
Product Identification  
=====

Product ID:NON REMOVABLE AIRCRAFT FINISH

MSDS Date:10/30/1991

FSC:8010

NIIN:00-181-7859

MSDS Number: BMBSZ

=== Responsible Party ===

Company Name:MAGRUDER COLOR CO. INC.

Address:1029 NEWARK AVE

City:ELIZABETH

State:NJ

ZIP:07201

Country:US

Info Phone Num:201-242-1300

Emergency Phone Num:

201-242-1300

Preparer's Name:DARREN BIANCHI

CAGE:53979

=== Contractor Identification ===

Company Name:MAGRUDER COLOR CO. INC.

Address:1029 NEWARK AVE

Box:City:ELIZABETH

State:NJ

ZIP:07201

Country:US

Phone:201-242-1300

CAGE:53979

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DYED POLYMER

Fraction by Wt: \*

Other REC Limits:PROPR

IETARY

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 32.1%\*

Other REC Limits:\*32.4%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-47-8

RTECS #:GA5504000

Fraction by Wt: 5.6%

Other REC Limits:NONE SPECIFIED

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA

CAS:64742-89-8

Fraction by Wt: 2.4%\*

Other REC Limits:\*2.6%

Ingred Name:CUMENE

CAS:98-82-8

RTECS #:GR857

5000

Fraction by Wt: 2.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM;150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE

CAS:95-63-6

RTECS #:DC3325000

Fraction by Wt: 1.7%

Other REC Limits:NONE SPECIFIED

===== Fire Fighting Measures =====

Flash

Point Method:PMCC

Flash Point:75.0F,23.9C

Lower Limits:1

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST POTENTIAL HARMFUL AND/OR IRRITATING FUMES.

Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK, MATERIAL CAN FORM EXPLOSIVE VAPORS WITH AIR.

=====  
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:220FTO330F

Vapor Density:>1 (AIR=1)

Spec Gravity:1.1

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BRIGHTLY COLORED VISCOUS LIQUID. SWEET, AROMATIC ODOR.

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NO SPECIFIC INCOMBATIBILITY, BUT AS WITH ALL ORGANIC MATERIALS, AVOID CONTACT

WITH STRONG CHEMICAL OXIDIZING AGENTS.

Stability Condition to Avoid:THERMAL DECOMPOSITION MAY PRODUCE TOXIC OXIDES OF CARBON, SULFUR AND/OR NITROGEN.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

d

ocument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.