View NSN Online: https://aerobasegroup.com/nsn/5970-00-242-0505

## DOW CORNING CORP -- 3145 RTV ADHES. SEALANT-CLEAR -- 5970-00-242-0505

============= Product Identification ========================

Product ID:3145 RTV ADHES. SEALANT-CLEAR

MSDS Date: 10/04/1985

FSC:5970

NIIN:00-242-0505

Kit Part:Y

MSDS Number: BMBVB === Responsible Party ===

Company Name: DOW CORNING CORP Address: 3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI ZIP:48640 Country:US

Info Phone Num:517-496-5900 0R 517-49

6-6000

Emergency Phone Num:517-496-5900 Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997 Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name: DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI ZIP:48611 Country:US

Phone:517-496-4388

CAGE:71984

======= Composition/Information on Ingredients ========

Ingred Name: METHOXYS

ILANE Fraction by Wt: 7% Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM (MEOH-MFR) ACGIH TLV:200 PPM (MEOH-MFR)
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-EYE:MAY IRRITATE WITH SLIGHT PAIN,REDNESS & POSSIBLE MINOR CORNEAL INJURY.SKIN:PROLONGED/REPEATED CONTACT MAY IRRITATE SLIGHTLY.INHALE:NO IRRITATION/INJURY LIKELY FROM RELATIVELY SHORT EXPOSURE. ORAL:AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS SHOULD NOT CAUSE INJURY.CHRONIC-NO KNOWN ADVERSE HEALTH EFFECTS. Effects of Overexposure:MAY IRRITATE EYE WITH SLIGHT PAIN, REDNESS & POSSIBLE MINOR CORNEAL INJURY. PROLONGED/REPEATED SKIN CONTACT MAY IRRITATE SLIGHTLY. NO IRRITATION/INJURY LIKELY FROM RELATIVELY SHORT EXPOSURE BY INHALAT ION. AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS SHOULD NOT CAUSE INJURY. Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL, MAY AGGRAVATE ALLERGIC CONDITIONS ON CERTAIN PEOPLE.
======================================
First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.INHALED:REMOVE TO FRESH AIR.EYES:FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN.SKIN:WIPE EXCESS OFF.WASH SKIN WITH SOAP & WATER.ORAL:NO PROBLEM.
======================================
Flash Point Method:OC Flash Po int:>250F,>121C Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:NONE KNOWN.
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT TO TAKE CARE

OF ANY OIL-LIKE RESIDUES.
Neutralizing Agent:N

OT APPLICABLE.
=========== Handling and Storage =============
Handling and Storage Precautions:STORAGE-STORE IN COOL, VENTILATED PLACE BELOW 90F/32C, AWAY FROM MOISTURE.  Other Precautions:THIS PRODUCT LIBERATES METHANOL WHEN EXPOSED TO WATER OR HUMID AIR. DO NOT BREATHE MIST OR VAPORS. AVOID CONTACT WITH EYES AND SKIN. WASH HANDS BEFORE EATING OR DRINKING. WORK WITH ADEQUATE VENTILATIO N. IF METHANOL VAPORS > 200PPM, USE SCBA.
====== Exposure Controls/ Personal Protection =========
Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE.  Ventilation:MECHANICAL (GENERAL) VENTILATION IS RECOMMENDED. LOCAL EXHAUST MAY BE NEEDED.  Protective Gloves:WASHING IS ADEQUATE  Eye Protection:SAFETY GLASSES, AS A MINIMUM  Other Protective Equipment:EYE WASH STATION.LONG SLEEVE CLOTHING TO MINIMIZE SKIN CONTACT.  Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURE  S. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.  Supplemental Safety and Health  THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED TEMPERATURES OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS.
=========== Physical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:>300F,>149C Vapor Pres: