View NSN Online: https://aerobasegroup.com/nsn/6850-00-142-9409

SHERWIN-WILLIAMS CO SPRAYON PRODUCTS DIV -- 00711 PENETRANT-LUBRICANT

6850-00-142-9409

Product ID:00711 PENETRANT-LUBRICANT

MSDS Date:06/18/1991

FSC:6850

NIIN:00-142-9409

MSDS Number: BMBZS

=== Responsible Party ===

Company Name: SHERWIN-WILLIAMS CO SPRAYON PRODUCTS DIV

Address:26300 FARGO AVE City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:US

Info Phone

Num:216-292-7400

Emergency Phone Num:216-292-7400

CAGE:DO642

=== Contractor Identification ===

Company Name: SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709 City:SOLON State:OH

ZIP:44139-3908 Phone:216-292-7400

CAGE:DO642

Company Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE Box:City:BEDFORD HEIGHTS

State:OH ZIP:44146 Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

======= Composition/Information on Ingredients ========

Ingred Name: N-BUTOXYETHANOL

CAS:111-76-2

Fraction by Wt: < 5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:25 PPM ACGIH TLV:240 MG/M3

Ingred Name: NAPHTHA, MEDIUM ALIPHATIC

CAS:64742-88-7

Fraction by Wt: 60% %

Other REC Limits: NONE SPECIFIED

Ingred Name: GLYCERYL MONOOLEATE

CAS:25496-72-4 Fraction by Wt: < 5%

Other REC Limits: NONE SPECIFIED

Ingred Name: DISTILLATES, SOLVENT-REFINED LIGHT NAPHTHENIC

CAS:64741-97-5 RTECS #:PY8041000 Fraction by Wt: < 5%

Other REC Limits: 5.0 MG/M3

OSHA PEL:300 PPM

ACGI

H TLV:300 PPM

Ingred Name: BARIUM DINONYLNAPHTALNE SULFONATE

CAS:25619-56-1 Fraction by Wt: < 5% Other REC Limits:NONE SPECIFIED OSHA PEL:0.5 MG/M3 (AS BA) ACGIH TLV:0.5 MG/M3 (AS BA)

Ingred Name: REFINED HEAVY PARAFFINIC DISTILLATES

CAS:64741-88-4

Fraction by Wt: 15% %

Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PROPANE (PROPELLANT)

CAS:74-98-6

RTECS #:TX2275000 Fraction by Wt: 20% %

Other REC Limits: 1800 MG/M3

OSHA PEL:1000 PPM

ACGIH TL

V:ASPHYXIANT; 9192
========= Hazards Identification ===========
LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IN A CONFINED AREA VAPORS IN HIGH CONCENTRATIONS ARE ANESTHETIC. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. HARMFUL OR FATAL IF SWALLOWED. REPORTS HAVE
ASSOCIATED REPEATED AND PROLONGED OVEREXOSUR E TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE, ALSO KIDNEY AND LIVER DAMAGE.
Explanation of Carcinogenicity:THIS PRODUCT IS NOT CONSIDERED TO BE A CARCINOGEN BY NTP, IARC OR OSHA OR NIOSH. Effects of Overexposure:OVER-EXPOSURE MAY RESULT IN LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. Medical Cond Aggravated by Exposure:NONE ESTABLISHED
======================================
First Aid:BREATHING: REMOVE PATIENT TO FRE SH AIR. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. SWALLOWING: CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.
======================================
Flash Point Method:TOC

Flash Point: