

CAAP CO INC -- CAAPCOAT AS-P108 CATALYST -- 8010-00-459-1756

=====  
Product Identification  
=====

Product ID:CAAPCOAT AS-P108 CATALYST

MSDS Date:11/01/1991

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BMCCV

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Pre

parer's Name:CHRISTINE L. SLEDGE

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 65.9%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM;150 PPM STEL

ACGIH TLV:100 PPM;150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

In

gred Name:METHYLISOBUTYLKETONE (SARA 313)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 23.9%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TRIETHYLENE DIAMINE  
CAS:280-57-9  
RTECS #:HM0354200  
Fraction by Wt: 3.4%  
Other REC Limits:NONE SPECIFIED

Ingred Name:DIPROPYLENE GLYCOL  
CAS:110-98-5  
RTECS #:UB8785000  
Fraction by Wt: 6.8%  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identifica  
tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE  
EYES/IRRITATE SKIN. RESPIRATORY IRRITATION UPON INHALATION.  
CHRONIC: REPEATED/PROLONGED EXPOSURE CAN CAUSE:  
HEADACHES/NAUSEA/VOMITING/COMA. HIGH CONCENTRATIONS CAUSES/PROLONG  
ED EXPOSURE: NEURAL DYSFUNCTION/KIDNEY/LIVER DAMAGE.  
Effects of Overexposure:VAPOR: BURNING EYES/HEADACHE/DIZZIN  
ESS/THROAT  
IRRITATION/LOSS OF APPETITE/NAUSEA/VOMITING. CONTACT: IRRITATION OF  
SKIN/BURNING OF SKIN/EYES.  
Medical Cond Aggravated by Exposure:PREEXISTING  
ALLERGIES/EYE/SKIN/RESPIRATORY DISORDERS.

=====  
First Aid Measures =====

First Aid:EYES: FLUSH W/WTR 15 MIN LIFT LIDS. IMMED MED ATTEN. SKIN:  
WASH W/SOAP/WATER. REMOVE CONTAM CLOTH. IRRITATE PERSISTS/SIGNS  
EXPOSURE EXIST IMMED MED ATTEN. INHALE: MOVE-FRESH AIR. ARTIF  
RSPRTN NO BREA

T H. IMMEDIATE MED ATTENTION. INGESTION: IMMEDIATE MED ATTENTION. NO VOMITING. IF VOMITING OCCURS KEEP VICTIMS HEAD BELOW HIPS--PREVENT BREATHING VOMITUS INTO LUNGS. CHEMICAL PNEUMONITIS/PULMONARY EDEMA/HEMORRHAGE.

===== Fire Fighting Measures =====

Flash Point Method: TOC

Flash Point: 68.0F, 20.0C

Lower Limits: 1

Upper Limits: 8

Extinguishing Media: WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE. DO NOT USE DIRECT WATER STREAM.

Fire Fighting Procedures: FIREFIGHTERS WEAR SCBA/FULL PROTECTIVE

CLOTHING. USE WATER TO COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: FLAMMABLE LIQUID. NO WATER ACCUMULATION; PRODUCT MAY FLOAT ON TOP MAY REIGNITE. NO IGNITION SOURCES; PRODUCT HEAVIER THAN AIR, MAY TRAVEL, FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures: NO IGNITION SOURCES/SMOKING. PROTECTIVE EQUIP: SOLVENT RESISTANT GLOVES/APRON/BOOTS/SCBA IN PRESSURE DEMAND MODE/SUPPLIED AIR RESPIRATOR. CONTAIN SPILL W/ABSORB MATERIAL. CLEAN UP ABSORB CONTAIN SECURELY. SWEEP/WET MOP W/SOAP/WATER. VENT AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH APPROVED RESPIRATOR FOR VAPOR/MIST EMISSION LEVELS AT POINT OF USE: INCLUDING FACEPIECE/PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPORS/MISTS/SELF-CONTAINED BREATHING APPARATUS IN PRESSURE DEMAND MODE/SUPPLIED AIR RESPIRATOR

Ventilation: SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS BELOW PEL'S. DESIGNED TO DRAW AIR PAST OPERATOR, THEN PAST SOURCE OF VAPOR\*

Protective Gloves: SOLVENT RESISTANT GLOVES

Eye Protection: SOLVENT RESISTANT SAFETY GOGGLES/GLASSES

Other Protective Equipment: SOLVENT RESISTANT APRON. DO NOT WEAR CONTACT LENSES, CONTRIBUTE TO SEVERITY OF EYE INJURY. EYEWASH/SAFETY SHOWER NEARBY.

Work Hygienic Practices: WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH WELL WITH SOAP AND WATER AFTER HANDLING

ING THE PRODUCT.

Supplemental Safety and Health

KEY1:F3. KIT CONSISTS OF EIGHT PARTS. PART ONE HAS PNI I, PART TWO HAS PNI J, PART THREE HAS PNI K ... THROUGH PNI P, SAME NSN. FORMULA CHANGED.

===== Physical/Chemical Properties =====

HCC:F7

Boiling Pt:B.P. Text:241FTO281F

Vapor Pres:8

Vapor Density:3.6

Spec Gravity:0.869 (WATER=1)

pH:10

Viscosity: