

ITW DEVCON CORP -- SILITIE RTV SILICONE-CLEAR, WHITE, AND HIGH -- 8040-01-193-3312

=====  
Product Identification  
=====

Product ID:SILITIE RTV SILICONE-CLEAR, WHITE, AND HIGH

MSDS Date:12/14/1989

FSC:8040

NIIN:01-193-3312

MSDS Number: BMCGB

=== Responsible Party ===

Company Name:ITW DEVCON CORP

Address:30 ENDICOTT ST

City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Info Phone Num:508-777-1100

Emerge

ncy Phone Num:800-424-9300 CHEMTREC

CAGE:EO352

=== Contractor Identification ===

Company Name:DEVCON CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Phone:1-508-777-1100

CAGE:16059

Company Name:ITW DEVCON CORP

Address:30 ENDICOTT ST

City:DANVERS

State:MA

ZIP:01923

Country:US

Phone:508-777-1100

CAGE:EO352

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYLACETOXYSILANE (SKIN, EYE, RESPIRATORY IRRITANT) (TLV  
SHOWN APPLIES TO

ACETIC ACID).  
CAS:4253-34-3  
RTECS #:VV4500000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:10 PPM

Ingred Name:ETHYLACETOXYSILANE (SKIN, EYE, RESPIRATORY IRRITANT) (TLV  
SHOWN APPLIES TO ACETIC ACID).

CAS:17689-77-9  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:10 PPM

Ingred Name:VOC: 15,000 PPM (ACETIC ACID); EXPOSURE  
TIME: HOURS. INGESTION OF SUBSTANTIAL AMOUNTS MAY CAUSE INJURY.  
CHRONIC: NO DATA.

Medical Cond Aggravated by Exposure:NONE REPORTED

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL  
ATTENTION. SKIN: WIPE OFF AND FLUSH WITH WATER. INHALATION: REMOVE  
TO FRESH AIR. OBTAIN IMMEDIATE MEDICAL ATTENTION. INGESTION: OBTAIN  
IMMEDIATE M EDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:>250F,>121C  
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.  
F  
ire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:LARGE SPILLS: VENTILATE AREA. SCRAPE UP SPILL  
AND PUT IN MOISTURE-PROOF CONTAINERS. SCRUB AREAS OF SPILLS WITH  
DETERGENT AND WATER TO REMOVE VINEGAR ODOR.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELO

W 90F. RELEASES ACETIC ACID

ON CONTACT WITH MOISTURE OR WATER VAPOR. GOOD VENTILATION. NO BREATHING ACETIC ACID VAPOR. NO CONTACT SKIN/EYES.

Other Precautions:THIS PRODUCT CONTAINS SILICON DIOXIDE. WHEN THE PRODUCT IS LIQUID THE SILICON DIOXIDE IS WET AND POSES NO HAZARD. HOWEVER IF THE SOLIDIFIED PRODUCT IS SANDED, SOME SILICON DIOXIDE MAY BE RELEASED. TVL 10 MGM3 IN AIR.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO PROTECT

IVE GEAR NEEDED IN WELL-VENTILATED

AREAS. ELSEWHERE WEAR NIOSH APPROVED ORGANIC ACID VAPOR RESPIRATOR.

Ventilation:SUFFICIENT TO MAINTAIN EXPOSURE LEVELS BELOW TLV. GENERAL

AREA VENTILATION IS USUALLY ADEQUATE. IN CONFINED AREAS OR

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:LONG SLEEVE AND OTHER PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

FOR HIGH VOLUME USES OF THE SILICONES, LOCAL EXHAUST IS RECOMMENDED.

=

=====  
===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>300

Vapor Pres:1

Spec Gravity:1.04

pH:3-4

Evaporation Rate & Reference: