View NSN Online: https://aerobasegroup.com/nsn/9150-00-082-2591

MOBIL OIL CORP -- DTE OIL HEAVY MEDIUM -- 9150-00-082-2591

============= Product Identification ==============

Product ID:DTE OIL HEAVY MEDIUM

MSDS Date:06/19/1991

FSC:9150

NIIN:00-082-2591

MSDS Number: BMDLK === Responsible Party ===

Company Name: MOBIL OIL CORP Address: 3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001 Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411

/CHEMTREC 800-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name: LEEDS & NORTHRUP CO A UNIT OF GENERAL SIGNAL CORP

Address:SUMNEYTOWN PIKE

Box:City:NORTH WALES

State:PA ZIP:19454 Country:US CAGE:31922

Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA ZIP:22037 Country:US

Phone: 800-662-4525/856-224-4644

CAGE:3U728

====== Composition/Information on Ingredients ========

Ingred Name: DISTILLATES, HYD

ROTREATED HEAVY PARAFFINIC CAS:64742-54-7 RTECS #:PY8035500
Fraction by Wt: >95% Other REC Limits:NONE SPECIFIED OSHA PEL:300 PPM ACGIH TLV:300 PPM
========== Hazards Identification ============
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EFFECTS OF OVEREXPOSURE: SLIGHT SKIN IRRITATION.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IA
RC, NTP OR OSHA AS A CARCINOGEN. Effects of Overexposure:SLIGHT SKIN IRRITATION
======================================
First Aid:EYE-FLUSH WITH WATER. SKIN-WASH AREA WITH SOAP & WATER. INHALE- NOT EXPECTED TO BE A PROBLEM. INGEST-NOT EXPECTED TO BE A PROBLEM. HOWEVER, IF GREATER THAN 1/2 LITER INGESTED, IMMEDIATELY GIVE 1-2 GLA SSES OF WATER & CALL A DOCTOR. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
======= Fire Fighting Measures ====================================
Flash Point Method:COC Flash Point:>400F,>204C Lower Limits:0.6 Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF. Unusual Fire/Explosion Hazard:NONE
======================================
Spill Releas

e Procedures:ADSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY.
======================================
Handling and Storage Precautions:STORAGE-STORE IN COOL,DRY WELL VENTILATED AREA AWAY FROM OXIDIZERS & FLAMES. Other Precautions:AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER HANDLING.
====== Exposure Controls/Personal Protection ========
Re spiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS IF NEEDED. Ventilation:GENERAL VENTILATION Protective Gloves:RUBBER - OPTIONAL Eye Protection:SAFETY GLASSES Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD BE FOLLOWED. Supplemental Safety and Health FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE P/N A UNDER THE SAME NSN.
===== ======= Physical/Chemical Properties ==================
HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: