

GEO PFAU'SONS CO, INC -- PEACOCK EWS LARD OIL -- 9150-00-231-9054

=====
Product Identification
=====

Product ID:PEACOCK EWS LARD OIL

MSDS Date:10/22/1992

FSC:9150

NIIN:00-231-9054

MSDS Number: BMDNS

=== Responsible Party ===

Company Name:GEO PFAU'SONS CO, INC

Address:800 WALL STREET

Box:7

City:JEFFERSONVILLE

State:IN

ZIP:47130-3619

Country:US

Info Phone Num:812-283-6697

Emergency Phone Num:812-28

3-6697

CAGE:KO733

=== Contractor Identification ===

Company Name:GEO PFAU'SONS CO, INC

Address:800 WALL STREET

Box:7

City:JEFFERSONVILLE

State:IN

ZIP:47130-3619

Country:US

Phone:812-283-6697

CAGE:KO733

Company Name:GEO.PFAU'S SONS CO,INC.

Address:800 WALL STREET

Box:7

City:JEFFERSONVILLE

State:IN

ZIP:47130-3619

Country:US

Phone:812-283-6697

CAGE:2W231

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-

7608
CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:LARD OIL (MFR LISTED CAS # AS 8016-28-2)
CAS:8016-28-2
Fraction by Wt: 100% %
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: AS RECEIVED, MATERIAL IS NOT
KNOWN TO BE ACUTELY TOXIC. HOWEVER, WHEN OVERHEATED, PEACOCK EWS
LARD OIL WILL PRODUCE ACROLEIN AND OTHER CARBON COMPOUNDS WHICH
MAY CAUSE BURNING OF THE EYES AND RESPIRATORY DISCOMFORT. CHRONIC:
NO KNOWN CHRONIC TOXIC EFFECTS.
Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS
CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.
Effects of Overexposure:EYES: TEARING, BLURRED VISION, DISCOMFORT.
INHALED: COUGHING, WHEEZING, SNEEZING, SHORTNESS OF BREATH.
Medical Cond Aggravated by Exposure:NONE
SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHALATION: MOVE AFFECTED SUBJECT TO FRESH AIR AND CONSULT A
PHYSICIAN IF IRRITATION PERSISTS. INGESTION: NOT ANTICIPATED TO BE
TOXIC. MAY HAVE A LAXATIVE EFFECT. CONSULT A PHYSICIAN. SKIN: WHEN
MOLTEN OR HEATED, WILL CAUSE OIL-TYPE BURNS.TREAT AS SUCH. WASH
AFFECTED SKIN AREAS WITH SOAP AND WATER. EYES: FLUSH WITH WATER AND
CONSULT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>500F,>260C
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:USE NO WATER. TREAT AS AN OIL FIRE. USE CARBON
DIOXIDE, FOAMITE, SAND OR SODIUM BICARBONATE.
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS AND PROTECTIVE GEAR WHEN FIGHTING CHEMICAL
FIRES.
Unusual Fire/Explosion Hazard:COMBUSTION GENERATES TOXIC FUMES
CONTAINING CARBON OXIDES.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SPILL AREAS MAY BE SLICK OR SLIPPERY. USE CARE TO AVOID FALLS OR OTHER ACCIDENTS. CONTAIN SPILLS IMMEDIATELY WITH INERT MATERIALS. MATERIAL CAN BE RECOVERED FROM THE GROUND BY PUMP, SHOVEL AND/OR ABSORPTION. KEEP OUT OF WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:MAINTAIN TEMPERATURE AT A MAXIMUM OF

100F FOR STORAGE. AVOID STORAGE AND TRANSFER FACILITIES CONSTRUCTED OF COPPER, COPPER ALLOYS.

Other Precautions:MATERIAL IS BIODEGRADABLE, PRODUCING A HIGH B.O.D. WHEN EMULSIFIED IN WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NEEDED ONLY AT ELEVATED TEMPERATURES--USE AN OSHA OR NIOSH APPROVED RESPIRATOR.

Ventilation:AT AMBIENT TEMPERATURES GENERAL (MECHANICAL) VENTILATION IS SUFFICIENT. LOCAL EXHAUST IS RECOMMENDED AT ELEVATED TEMPS.

Protective Gloves:AT ELEVATED TEMPS, OIL RESISTANT THERMAL

Eye Protection:SAFETY GLASSES OR FACE SHIELD

Other Protective Equipment:WHEN PRODUCT IS HEATED, NORMAL

OIL-RESISTANT THERMAL PROTECTION IS RECOMMENDED.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

=

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:45.0F,7.2C

Vapor Pres:1 (AIR=1)

Spec Gravity:0.905 - 0.915

Viscosity:190 - 210 SUS

Evaporation Rate & Reference: