View NSN Online: https://aerobasegroup.com/nsn/6850-00-949-1397

UNI-KEM INTERNATIONAL INC. -- P-S-120B TYPE II SCALE REMOVING COMPOUND 6850-00-949-1397

Product ID:P-S-120B TYPE II SCALE REMOVING COMPOUND MSDS Date:05/04/1993 FSC:6850 NIIN:00-949-1397 MSDS Number: BMGQK === Responsible Party === Company Name: UNI-KEM INTERNATIONAL INC. Address:513 HICKORY AVE **City:HARAHAN** State:LA ZIP:70123 Country:US Info Phone Num:504-738 -1623 Emergency Phone Num:504-738-1623 CAGE:4S446 === Contractor Identification === Company Name: UNI-KEM INTERNATIONAL Address:1001 HARIMAW COURT EAST Box:City:METAIRIE State:LA ZIP:70001 Country:US Phone:504-835-7600/FAX:504-835-7608 CAGE:4S446 Ingred Name: PHOSPHORIC ACID CAS:7664-38-2 RTECS #:TB6300000

Fraction by Wt: 40.0% OSHA PEL:1 MG/M3/3 STEL ACGIH TLV:1 MG/M3/3 STEL; 8990 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ing

red Name:HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA III) CAS:7647-01-0 RTECS #:MW4025000 Fraction by Wt: 3.0% Other REC Limits:1 MG/M3 OSHA PEL:C 5 PPM ACGIH TLV:C 5 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATION TO EYES , NOSE AND THROAT Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure:EYE IRRITATION, NOSE/THROAT IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH WITH LOTS OF WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION

: IMMEDIATELY ADMINISTER LARGE QUANTITIES OF WATER OR MILK. DO NO T INDUCE VOMITING. THEN ADMINISTER MILKOF MAGNESIA (20 ML). IF VOMITING OCCURS, GIVE DEMULCENTS, SUCH AS MILK OR BEATEN EGGS AT INTERVALS OF 2 HOURS UNTIL VOMITING STOPS. GET MEDICAL ATTENTION.

Flash Point:NONFLAMMABLE

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE

Fire Fighting Procedures: FIREMAN SHOULD WEAR AS MINIMUM PROTECTION, ALL PUR

POSE CANISTER GAS MASK APPROVED BY THE U.S. BUREAU OF MINES. Unusual Fire/Explosion Hazard:PRODUCT CAN REACT WITH METALS TO LIBERATE HYDROGEN, A FLAMMABLE GAS, IN SMALL AMOUNTS.

Spill Release Procedures:NEUTRALIZE WITH WEAK BASIC (ALKALINE) MATERIAL. FLUSH WITH PLENTY OF WATER. Neutralizing Agent:WEAK BASIC (ALKALINE) SOLUTION

Handling and Storage Pr

ecautions: CONTAINS MINERAL ACIDS. VAPOR HARMFUL. AVOID CONTACT WITH SKIN. DO NOT GET IN EYES. HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN. Other Precautions: CAUSES SEVERE BURNS. STORE DRUMS AWAY FROM HEAT AND OUT OF DIRECT SUNLIGHT. IN HOT WEATHER, LOOSEN PLUGS OF STORED DRUMS WEEKLY OR SOONER IF NEEDED. READ ALL INSTRUCTIONS CAREFULLY **BEFORE USING.** Respiratory Protection: IF VENTILATION DOES NOT MAI NTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION. Ventilation:LOCAL EXHAUST IF NEEDED. Protective Gloves: RECOMMENDED -- RUBBER OR NEOPRENE Eye Protection: GOGGLES Other Protective Equipment: RUBBER APRON, EMERGENCY SHOWER AND EYE WASH STATION Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING. Supplemental S afety and Health NONE SPECIFIED BY MANUFACTURER. HCC:C1 Boiling Pt:B.P. Text:224F,107C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:LOW Vapor Density:> 1 Spec Gravity:1.290 Evaporation Rate & amp; Reference: LOW Solubility in Water:COMPLETE Appearance and Odor: CLEAR, LIQUID, MILD ODOR, WATER WHITE TO LIGHT YELLOW Percent Volatiles by Volume:58%

Stabil

ity Indicator/Materials to Avoid:YES CAN REACT WITH METALS TO LIBERATE HYDROGEN IN SMALL AMOUNTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:OXIDES OF PHOSPHOROUS

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Discla

imer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.