

HR TEXTRON INC, APCO & FILTER PRODUCT GROUP -- P/N 826200-107 -- 1680-01-123-1596

=====
Product Identification
=====

Product ID:P/N 826200-107

MSDS Date:10/01/1985

FSC:1680

NIIN:01-123-1596

MSDS Number: BMGSC

=== Responsible Party ===

Company Name:HR TEXTRON INC, APCO & FILTER PRODUCT GROUP

Address:10445 GLENOAKS BLVD

City:PACOIMA

State:CA

ZIP:91331-1609

Country:US

Info Phone Num:818-896-5291

Eme

Agency Phone Num:818-896-5291

CAGE:96124

=== Contractor Identification ===

Company Name:HR TEXTRON INC, APCO & FILTER PRODUCT GROUP

Address:10445 GLENOAKS BLVD

Box:City:PACOIMA

State:CA

ZIP:91331-1609

Country:US

Phone:818-896-5291

CAGE:96124

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

Box:City:WILSON

State:NC

ZIP:27893-9604

Country:US

Phone:252-237-7004

CAGE:61423

=====
Composition/Information on Ingredients
=====

Ingred Name:CARBON DIOXI

DE
CAS:124-38-9
RTECS #:FF6400000
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CARBON DIOXIDE IS THE MOST POWERFUL
CEREBRAL VASODILATOR KNOWN. INHALING LARGE CONCENTRATIONS CAUSES
RAPID CIRCULATORY INSUFFICIENCY, LEADING TO COMA & DEATH. CHRONIC,
HARMFUL EFFECTS ARE NOT
KNOWN FR OM REPEATED INHALATION OF LOW (3-5
MOLAR %) CONCENTRATIONS.
Effects of Overexposure:INHALATION-LOW CONCENTRATIONS (3-5 MOLAR %)
CAUSE INCREASED RESPIRATION & HEADACHE. EIGHT TO 15 MOLAR %
CONCENTRATIONS CAUSE HEADACHE, NAUSEA & VOMITING WHICH MAY LEAD TO
UNCONSCIOUSNESS IF NOT MOVED TO OPEN AIR OR GIVEN OXYGEN. HIGHER
CONCENTRATIONS CAUSE RAPID CIRCULATORY INSUFFICIENCY LEADING TO
COMA & DEATH.

=====
===== First Aid Measures =====

==

First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF
OVEREXPOSURE TO CARBON DIOXIDE. RESCUE PERSONNEL SHOULD BE EQUIPPED
W/SELF-CONTAINED BREATHING APPARATUS. CONSCIOUS PERSONS SHOULD BE
MOVED TO UNC ONTAMINATED AREA & INHALE FRESH AIR. UNCONSCIOUS
PERSON SHOULD BE MOVED TO UNCONTAMINATED AREA, GIVEN MOUTH-TO-MOUTH
RESUSCITATION & SUPPLEMENTAL OXYGEN.

=====
===== Fire Fighting Measures =====

Extinguishing Media:NONFLAMMABLE, INERT
GAS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE
APPROPRIATE PROTECTIVE EQUIPMENT. IF LEAK IS IN USER'S EQUIP, BE
CERTAIN TO PURGE PIPING W/AN INERT GAS PRIOR TO ATTEMPTING REPAIRS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL-VENTILATED AREAS.
PROTECT CYLINDERS FROM DAMAGE.FULL/EMPTY CYLINDERS SHOULD BE
SEGRE

GATED. DO NOT DRAG, SLIDE OR ROLL CYLINDERS.

Other Precautions:COMPRESSED GAS CYLINDERS SHOULD NOT BE REFILLED EXCEPT BY QUALIFIED PRODUCERS OF COMPRESSED GASES. SHIPMENT OF COMPRESSED GAS CYLINDERS WHICH HAS NOT BEEN FILLED BY THE OWNER OR W/HIS WRITTEN CONSENT IS A VIOLATION OF FEDERAL LAW (49CFR).

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:POSITIVE PRESSURE AIR LINE W/MASK OR SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILA
BLE FOR
EMERGENCY USE.

Ventilation:YES, TO PREVENT ACCUMULATION ABOVE THE TWA.

Protective Gloves:ANY MATERIAL

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:SAFETY SHOES

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-109F,-79C

Vapor Pres:@70F,21.1C

Spec Gravity:1.53

Solubility in Water:@68F, 20C

Appearance and Odor:COLORLESS, ODORLESS GAS.

Percent Volatiles by Volume:N/RNK

Corrosion Rat

e:N/RNK

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products:CARBON MONOXIDE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF RESIDUAL OR UNUSED QUANTITIES. RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, W/ANY VALVE OUTLET PLUGS CAPS SECURED & VALVE PROTECTION CAP IN PLACE TO THE MANUFACTURER.

Disclaimer (prov

ided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.