

ACCUMETRIC INC -- A-106 ADHESIVE PART B, M/00102-0131 -- 8040-01-157-6451
===== Product Identification =====

Product ID:A-106 ADHESIVE PART B, M/00102-0131

MSDS Date:06/22/1988

FSC:8040

NIIN:01-157-6451

MSDS Number: BMGSS

=== Responsible Party ===

Company Name:ACCUMETRIC INC

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:502-769-3385

CAGE:

58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

===== Composition/Information on Ingredients =====

Ingred Name:METHYLPOLYSILOXANE

Fraction by Wt: 100%

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicit

y:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: MAY CAUSE TEMPORARY DISCOMFORT;
SKIN-NO KNOWN SIDE EFFECT; INHAL: SLIGHT IRRITANT/PAIN TO EYES OR
RESPIRATORY PASSAGES.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MIN. SKIN: WIPE OFF
AND F

LUSH WITH WATER. INHAL: REMOVE TO FRESH AIR. SUPPORT BRTHG.
(GIVE O*2/ARTF RESP) . INGEST: CALL MD IMMED .

=====
Fire Fighting Measures
=====

Flash Point Method:CC

Flash Point:150F,66C

Extinguishing Media:WATER, WATER FOG, CO*2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:CONTACT WITH HOT ABSORBENT MATERIAL MAY
CAUSE SPONTANEOUS COMBUSTION-THIS MAY BE FIRE
HAZARD.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN
FOR SALVAGE AND DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:PRODUCT IS COMBUSTIBLE. STORE IN DRY
AREA. WHEN CONTAINER IS OPEN, KEEP CLEAN AND DRY. USE REASONABLE
CARE AND CAUTION.

Other Precautions:UNCATALYZED/CATALYZED

SOLN OF PROD EVOLV MINUTE QTY

OF HYDROGEN GAS. DO NOT REPACKAGE/STORE IN UNVENTD CONTR. ADEQ VENT
WORK AREA TO PVNT ACCUMULATING GAS/SOLV VAP. TRACES OF FORMALDEHYDE
& OTHER THER M DECOMP PROD MAY FORM @ (SUPP DATA)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED. USE NIOSH/MSHA APPROVED
RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:MECHANICAL RECOMMENDED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protecti

on:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:ABOVE PREC ARE FOR ROOM TEMP HNDLG, USE @
ELEVATED TEMP MAY REQUIRE ADDED PREC; WASH @ MEAL TIME & @ END
(SUPP DATA)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

OTHER PREC:TEMPERATURES ABOVE 150C IN PRESENCE OF AIR. PROVIDE ADEQUATE
VENTILATION WHEN HANDLING @ ELEVATED TEMPERATURES. OTHER PROT
EQUIP:OF WORK SHIFT IS ADEQUATE.

===== Physical/Chemical Properties =====

=====

HCC:V4

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: