

TECHNOLUBE PRODUCTS CO -- MIL-F-17111 B POWER TRANSMISSION FLUID -- 9150-00-261-8318
===== Product Identification =====

Product ID:MIL-F-17111 B POWER TRANSMISSION FLUID

MSDS Date:10/31/1989

FSC:9150

NIIN:00-261-8318

MSDS Number: BMQBC

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS CO

Address:5814 E 61ST ST

City:LOS ANGELES

State:CA

ZIP:90040-3412

Country:US

Info Phone Num:213-727-779

2

Emergency Phone Num:213-928-3311

Preparer's Name:RICHARD J. EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE (TOTAL PERCENTAGE
OF ING. 1, 2, AND 3 IS 212F,>100C

Extinguishi

ng Media:USE WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL,
SAND OR EARTH. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS OPERATED IN+PRESSURE.
COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:WILL RELEASE FLAMMABLE VAPORS WHICH CAN
BURN OR BE EXPLODED IN CONFINED SPACES IF EXPOSED TO SOURCE OF
IGNITION.

===== Accidental Release Me

asures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION. RECOVER FREE LIQUID. ADD INERT ABSORBENT SUCH AS EARTH,SAND, OR VERMICULITE TO SPILL AREA. COLLECT ABSORBENT. KEEP PRODUCT OUT OF WATER WAYS.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-KEEP CONTAINER IN COOL,DRY PLACE AWAY FROM EXCESSIVE HEAT,FLAMES & STRONG OXIDIZERS.

Other Precautions:AVOID CONT

ACT WITH SKIN, EYES, AND CLOTHING. WASH

THOROUGHLY AFTER HANDLING. LAUNDER CLOTHING BEFORE REUSE. AVOID INHALING VAPORS. EMPTY CONTAINERS OF THIS PRODUCT MAY BE HAZARDOUS DUE TO THE RETENTIO N OF RESIDUES AND VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE. IF TLV EXCEED, WEAR A NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST FAN IS RECOMMENDED TO MAINTAIN CONCENTRATION OF OIL MIST IN AIR B

ELOW RECOMMENDED TLV.

Protective Gloves:RUBBER/OIL RESISTANT GLOVES RECOMMENDED

Eye Protection:CHEMICAL SAFETY GOGGLES,FULL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

===

HCC:V6

Boiling Pt:B.P. Text:>392F,>200C

Vapor Pres:1

Spec Gravity:0.860

Evaporation Rate & Reference: