View NSN Online: https://aerobasegroup.com/nsn/8040-00-851-0211

POLYMERIC SYSTEMS, INC. -- PSI-690 PRIMER -- 8040-00-851-0211

Product ID:PSI-690 PRIMER MSDS Date:12/14/1990

FSC:8040

NIIN:00-851-0211

Kit Part:Y

MSDS Number: BMQHG === Responsible Party ===

Company Name: POLYMERIC SYSTEMS, INC. Address: WHEATLAND AND MASON STREETS

City:PHOENIXVILLE

State:PA ZIP:19460 Country:US

Info Phone Num:215-935-1170 GOVT/RITA 404-331-5855

F

mergency Phone Num:215-935-1170

Preparer's Name: EF CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name: POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA ZIP:19460 Country:US

Phone:610-935-1170

CAGE:0KND3

======= Composition/Information on Ingredients ========

Ingred Name: ETHANOL

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 90%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

Ingred Name:METHANOL

CAS:67-56-1

RTECS

#:PC1400000 Fraction by Wt: 4%

Other REC Limits:NONE SPECIFIED OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ETHYL POLYSILICATE

CAS:68412-37-3 Fraction by Wt: 2-4%

Other REC Limits: NONE SPECIFIED

Ingred Name: VOC: 6.5 LBS/GAL; 780 GRAMS/LITER

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of C

arcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MUCOUS MEMBRANE IRRITATION, DROWSINESS, PROSTRATION, NARCOSIS; SKIN IRRITATION; EYE IRRITATION. CHRONIC: DAMAGE TO LIVER, KIDNEY AND PERIPHERAL & OPTIC

NERVE-JAUNDICE, EDEMA AND LOSS OF VISION.

Effects of Overexposure:IRRITATION OF MUCOUS MEMBRANES, HEADACHE, DROWSINESS, FATIGUE, NARCOSIS.

Medical Cond Aggravated by Exposure:EYE, SKIN AND RESPIRATORY DISORDERS AND IMPAIRED LIVER, KIDNEY AND OPTIC

& PERIPHERAL NERVE FUNCTIONS

MAY BE AGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:INHALE: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. SKIN: FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING. EYE: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR DROWSY. OTHERWISE, INDUCE VOMITING. GET MEDICAL ATTENTION.

==== Fire Fighting Measures ============
Flash Point Method:CC Flash Point:56.0F,13.3C Autoignition Temp:Autoignition Temp Text:793F Lower Limits:3.3 Upper Limits:19 Extinguishing Media:DRY CHEMICAL, FOAM, CO2, SAND, WATER SPRAY Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS OPERATED IN POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:SMOKE MAY CONTAIN HCL AS WELL AS NORMAL PARTIAL OXIDATION PRODUCTS OF HYDROCARBON COMBUSTION.
======================================
Spill Release Procedures:TAKE UP WITH ABSORBENT MATERIAL. STORE IN APPROPRIATE CONTAINER. AVOID PROLONGED INHALATION OF VAPOR OR CONTACT WITH LIQUID. WASH RESIDUES WITH LARGE AMOUNTS OF WATER.
======================================
Handling and Storage Precautions:AVOID IGNITION SOURCES: FLAME, SPARKS, EXTREME HEAT. STORE IN WELL VENTILATED AREA. Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED.
======================================
Respiratory Protection:IF LARGE AMOUNTS ARE USED IN A POORLY VENTILATED CLOSED SPACE, USE A CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE (NIOSH/MSHA APPROVED) TO PROTECT AGAINST ALCOHOL VAPORS.
Ventilation:LOCAL EXHAUST MAY BE REQUIRED IN CLOSED SPACES. RECOMMEND 10 CHANGES PER HOUR. Protective Gloves:RUBBER OR POLYETHYLENE Eye Protection:SAFETY GLASSES Supplemental Safety and Health
========= Physica

I/Chemical Properties =========
HCC:F3 Boiling Pt:B.P. Text:165F,74C Melt/Freeze Pt:M.P/F.P Text:-130F,-90C Decomp Temp:Decomp Text:>400F,>204C Vapor Pres:42 Vapor Density:1.8 Spec Gravity:0.80 pH:7 Viscosity:2 CPS @ 20C Evaporation Rate & amp; Reference:1.4 (BU AC=1) Solubility in Water:98% Appearance and Odor:COLORLESS LIQUID, PLEASANT ODOR Percent Volatiles by Volume:95
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES N ONE Stability Condition to Avoid:OPEN FLAMES, SPARKS, EXTREME HEAT Hazardous Decomposition Products:BY COMBUSTION: CO, HCL, AEROSOLS OF SILICA & TITANIA, INCOMPLETE COMBUSTION PRODUCTS.
======= Disposal Considerations ==========
Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of
Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.