

MASTER LUBRICANTS CO -- LUBRIKO M-6 GREASE -- 9150-00-946-9509

=====
Product Identification
=====

Product ID:LUBRIKO M-6 GREASE

MSDS Date:08/01/1991

FSC:9150

NIIN:00-946-9509

MSDS Number: BMQJS

=== Responsible Party ===

Company Name:MASTER LUBRICANTS CO

Box:411

City:WESTVILLE

State:NJ

ZIP:08093

Country:US

Info Phone Num:609-848-2880

Emergency Phone Num:609-848-2880

CAGE:76227

=== Contractor Ident

ification ===

Company Name:MASTER LUBRICANTS CO INC

Address:MEADOW AND JACKSON STS

Box:City:PHILADELPHIA

State:PA

ZIP:19148

Country:US

Phone:215-389-2680

CAGE:76227

=====
Composition/Information on Ingredients
=====

Ingred Name:STEARIC ACID, SODIUM SALT; (SODIUM STEARATE)

CAS:822-16-2

RTECS #:WI4725000

Fraction by Wt: 17-19%

Ingred Name:STEARIC ACID, CALCIUM SALT; (CALCIUM STEARATE)

CAS:1592-23-0

RTECS #:WI3000000

Fraction by Wt: 1%

Ingred Name:MINERAL OIL, PETROLEUM DISTIL

LATES, SOLVENT-REFINED HEAVY

PARAFFINIC; (MINERAL OIL)

CAS:64741-88-4

RTECS #:PY8040500

Fraction by Wt: 40-41%

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:SOLVENT, DEWAXED RESIDUAL OIL (PETROLEUM); (MINERAL OIL)

CAS:64742-62-7

Fraction by Wt: 40-41%

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO

Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN OR EYE
CONTACT MAY CAUSE MILD (TRANSIENT) IRRITATION.

Explanation of Carcinogenicity:MINERAL OIL:IARC -GROUP 1 (RTECS)

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INGEST: ADMINISTER VOLUMES OF WATER OR MILK AND GET MEDICAL

ATTENTION. SKIN: WIPE OFF AND WASH W/SOAP & WATER. EYES: FLUSH W/COPIOUS AMOUNTS OF WATER FOR A MINIMUM OF 15 MINUTES AND GET MEDICAL ATTENTION. INHAL: REMOVE FROM EXPOSURE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Extinguishing Media:DRY CHEMICAL, FOAM, WATER FOG, CO*2.

Fire Fighting Procedures:WATER MAY CAUSE FROTHING. WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual

Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN SAND OR INERT MATERIAL, SCOOP OR SWEEP UP AND REMOVE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE INDOORS, WITH LIDS IN PLACE AND AWAY FROM OPEN FLAMES OR DIRECT SUNLIGHT.

Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. IF NEEDED, USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NORMALLY NOT REQUIRED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE.

Work Hygienic Practices:FOLLOW NORMAL CLEANLINESS PROCEDURES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:365F,185C

Vapor Pres:10

Spec Gravity:0.9

Evaporation Rate & Reference: