

MOBIL OIL CORP -- MOBIL DELVAC 1200 SUPER 15W-40 -- 9150-00-186-6699

===== Product Identification =====

Product ID:MOBIL DELVAC 1200 SUPER 15W-40

MSDS Date:12/03/1991

FSC:9150

NIIN:00-186-6699

MSDS Number: BMQRV

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-424-9300

Emergency Phone Num:703-849-326

5 OR 212-883-4411

CAGE:1E969

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Address:530 EAST SWEDES FORD ROAD

Box:1031

City:VALLEY FORGE

State:PA

ZIP:19482

Country:US

Phone:703-849-3265

CAGE:1E969

Company Name:MOBIL OIL CORPORATION

City:PENNINGTON

State:NJ

ZIP:08534

Country:US

Phone:212-883-4411

CAGE:78253

===== Composition/Information on Ingredients =====

Ingred Name:SEVERELY SOLVENT REFINED AND SEVERELY HYDROTREATED MINERAL
BASE OILS.

Fraction by Wt: >90.0

%
Other REC Limits:5 MG/M3 OIL MIST

Ingred Name:POLYOLEFIN AMIDE ALKENEAMINE
Other REC Limits:NONE SPECIFIED

Ingred Name:BORONATED SUBSTITUTED SUCCINIMIDE
Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM SULFONATE OVERBASED
Other REC Limits:NONE SPECIFIED

Ingred Name:OLEFIN POLYMERS
Other REC Limits:NONE SPECIFIED

Ingred Name:BUTENE, HOMOPOLYMER
CAS:9003-29-6
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation
:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-INGESTION:NAUSEA, VOMITING.,
MINUTE AMOUNTS ASPIRATED INTO LUNGS MAY CAUSE PULMONARY INJURY AND
EVEN DEATH. INHALATION OF MIST MAY CAUSE CHEMICAL PNEUMONITIS.
EYE:IRRITATION. SKIN: IRRITATION, D EFATTING.
CHRONIC-SKIN:IRRITATION, DERMATITIS.
Effects of Overexposure:EYE-IRRITATION. SKIN-DRYNESS, IRRITATION.
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH EXIS
TING SKIN
DISEASES MAY BE AT INCREASED RISK.

=====
===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN.
IF IRRITATION OR REDNESS PERSIST CONSULT A PHYSICIAN. SKIN-REMOVE
CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. INGESTION: DO
NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. INHALATION OF
OIL MIST OR FUMES, REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF
NEEDED. GET MEDICAL HELP.

==

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>390F,>199C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:DO NOT USE WATER STREAM DIRECTLY. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard:DO NOT HANDLE OR STORE NEAR HEAT OR FLAMES. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

===== Accidental Release Measures =====

Spill Release Procedure

s:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. DIKE AND KEEP PRODUCT OUT OF SEWERS & WATER COURSES. PUT WASTE IN A CONTAINER FOR PROPER DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:MINIMIZE SKIN CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE NEAR EXTREME HEAT OR OPEN FLAMES.

Other Precautions:DO NOT CREATE MIST. DO NOT INHALE MIST OR VAPORS

PRODUCED AT HIGH TEMPERATURES. IF WORKING WITH MIST OR FUMES, NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPORS FILTER MUST BE WORN. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. IF WORKING WITH MIST OR FUMES, USE NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPOR FILTER.

Ventilation:NORMAL OR MECHANICAL

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING.

Work Hygienic Practices:WASH HANDS AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORKING AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: