

RIDGE TOOL COMPANY DIV EMERSON ELECTRIC -- RIDGID NUCLEAR THREAD CUTTING OIL. --  
9150-01-013-5281

=====  
Product Identification  
=====

Product ID:RIDGID NUCLEAR THREAD CUTTING OIL.

MSDS Date:09/29/1987

FSC:9150

NIIN:01-013-5281

MSDS Number: BMSYN

=== Responsible Party ===

Company Name:RIDGE TOOL COMPANY DIV EMERSON ELECTRIC

Address:400 CLARK STREET

City:ELYRIA

State:OH

ZIP:44035-6108

Country:US

|

Info Phone Num:216-323-5581

Emergency Phone Num:216-323-5581

CAGE:50893

=== Contractor Identification ===

Company Name:RIDGE TOOL COMPANY

Address:400 CLARK STREET

Box:City:ELYRIA

State:OH

ZIP:44036-2023

Country:US

Phone:800-519-3456

CAGE:50893

Company Name:UNITY SUPPLY COMPANY

Box:1249

City:BOLINGBROOK

State:IL

ZIP:60440-7249

Country:US

Phone:708-739-2538

CAGE:0SWA1

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PARAFFINIC MINERAL OIL

CAS:64742-50-3

OSHA PEL:5M

G/M\*3 (MIST)  
ACGIH TLV:5MG/M\*3 (MIST)

===== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:CAUSES IRRITATION. MAY BE SKIN  
DEFATTER UPON PROLONGED OR REPEATED CONTACT.  
Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS  
CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.  
Effects of Overexposure:OIL MIST INHALATION MAY  
CAUSE DIZZINESS, NAUSEA  
& DIFFICULTY IN BREATHING.  
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH SENSITIVE DRY  
SKIN.

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT:IMMEDIATELY FLUSH EYES WITH PLENTY OF  
WATER FOR AT LEAST 15 MINUTES,CALL A PHYSICIAN. WASH SKIN WITH SOAP  
& WATER. IF SWALLOWED,DO NOT INDUCE VOMITING. GET MEDICAL  
ATTENTION. REMOVE FLUID SOAKED CLOTHING & SHOES. LAUNDRER BEFORE  
REUSE. IF INHALED,REMOVE TO FRESH AIR & GIVE CPR IF NECESSARY. GET  
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:340F,171C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.  
Unusual Fire/Explosion Hazard:HOT VAPORS FORM EXPLOSIVE MIXTURES WITH  
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT USE WATER. SOAK UP WITH SAND, EARTH OR  
OTHER INERT MATERIAL. PUT IN A SUITABLE CONTAINER FOR DISPOSAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:LAUNDRER CONTAMINATED CLOTHING BEFORE  
REUSE. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING MIST OR

VAPORS.

Other Precautions:EMPTY CONTAINERS RETAIN PRODUCT RESIDUE. FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR IF EXPOSED TO HOT VAPOR OR MIST.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS REQD TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING.

Supp

lemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:480F,249C

Melt/Freeze Pt:M.P/F.P Text:0F,-18C MAX

Vapor Pres:0.01

Vapor Density:1

Spec Gravity:0.87

Evaporation Rate & Reference:1 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MILD PETROLEUM ODOR.

Percent Volatiles by Volume:0

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS AND OXIDANTS

Stability Condition to Avoid:SPARKS AND OPEN FLAMES

Hazardous Decomposition Products:CO, CO\*2, OXIDES OF SULFUR

=====  
===== Disposal Considerations =====

Waste Disposal Methods:BURY IN AN APPROVED LANDFILL OR INCINERATE IAW FEDERAL,STATE & LOCAL REGULATIONS. AVOID CONTAMINATION OF SEWERS & WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):  
This information i

s formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.