View NSN Online: https://aerobasegroup.com/nsn/9150-01-035-5391

HENKEL CORP POLYMERS DIV -- EMGARD 2984-E EP 75W-90 SYNTHETIC GEAR LUBR

9150-01-035-5391

Product ID:EMGARD 2984-E EP 75W-90 SYNTHETIC GEAR LUBR

MSDS Date:03/28/1991

FSC:9150

NIIN:01-035-5391

MSDS Number: BMSYV === Responsible Party ===

Company Name: HENKEL CORP POLYMERS DIV

Address:5325 S 9TH ST

City:LA GRANGE

State:IL

ZIP:60525-3602

Country:US

Info Phone Num:

312-579-6150

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name: ROBERT E. BORGERING

CAGE:1U766

=== Contractor Identification ===

Company Name: HENKEL CORP POLYMERS DIV

Address:5325 S 9TH ST Box:City:LA GRANGE

State:IL

ZIP:60525-3602

Country:US

Phone:708-579-6198

CAGE:1U766

Company Name: TULSTAR PRODUCTS INC Address: 1722 S CARSON, SUITE 2907

Box:City:TULSA

State:OK ZIP:74119 Country:US

Phone:918-587-7878/FAX -3297 (DAVID COOK)

CAGE:0F2M5

====== Composition/Information on Ingredien

Ingred Name:PROPRIETARY INGREDIENTS

Fraction by Wt: 100%

Other REC Limits: NONE SPECIFIED

========== Hazards Identification ================

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5000 MG/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MAY IRRIATE EYES AND SKIN.

CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity: IARC HAS DETERMINED THE

RE IS SUFFICIENT

EVIDENCE FOR THE CARCINOGENICITY IN EXPERIMENTAL ANIMALS OF USED MOTOR OIL.

Effects of Overexposure:EYES: REDNESS, BURNING SENSATION, ITCHING. SKIN: REDNESS, RASH.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS. INHALATION: REMOVE TO FRESH AIR & RESTORE

BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: MAY ACT AS A LAXATIVE. DO NOT INDUCE VOMITING. RELATIVELY NON-TOXIC UNLESS ASPIRATED.

========= Fire Fighting Measures ==============

Flash Point Method:COC

Flash Point:350F,177C

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. USE WATER FOG TO DISPERSE VAPORS.


Fire Fighti

ng Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

======== Accidental Release Measures ==========

Spill Release Procedures: CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES, REMOVE ALL SOURCES OF IGNITION. ABSORB



RNED IN AN APPROVED INCINERATOR
OR DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND
FEDERAL LAWS AND REGULATIONS. RECYCLE IF POSSIBLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.