

HULS AMERICA INC -- ANDEROL 786 SYN SEVERE DUTY GREASE -- 9150-00-926-1969

=====  
Product Identification  
=====

Product ID:ANDEROL 786 SYN SEVERE DUTY GREASE

MSDS Date:12/21/1990

FSC:9150

NIIN:00-926-1969

MSDS Number: BMTNT

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergenc

y Phone Num:201-980-6800

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

=====  
Composition/Information on Ingredients  
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE  
PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Rout

es of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS  
OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYES, NOSE, THROAT AND  
RESPIRATORY SYSTEM IRRITATION.  
Effects of Overexposure:MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE  
NAUSEA, AND VOMITING.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====  
=====

First Aid:CONTACT: WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH WATER  
FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION DEVELOPS.  
INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR  
OXYGEN IF NECESSARY. INGESTION: INDUCE VOMITING IF VICTIM IS  
CONSCIOUS. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN  
UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:COC  
Flash Point:>450F,>232C  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUID AND FIRE  
BY WATER FLOODING.  
Unusual Fire/Explosion Hazard:BURNING WILL PRODUCE TOXIC FUMES.  
EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH  
WATER SPRAY.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:WIPE UP SPILLS IMMEDIATELY.  
Neutralizing Agent:NONE

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:DO NOT USE GREASE ABOVE MAXIMUM  
RECOMMENDED OPERATING TEMPERATURE OF 450F. GREASE MAY SOFTEN SOME  
PLASTIC AND PAINT SURFACES.  
Other Precautions:NONE

=====  
===== Exposure Controls/Personal Protection =====  
=====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED  
RESPIRATORY PROTECTIVE EQUIPMENT.  
Ventilation:RECOMMENDED  
Protective G

loves:RECOMMENDED

Eye Protection:CHEMICAL SPLASH GOGGLES/ FACE SHIELD.

Other Protective Equipment:EYEWASH FOUNTAIN, SAFETY SHOWER. WASH  
CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING THIS MATERIAL.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>660F,>349C

Melt/Freeze Pt:M.P/F.P Text:>500F,>260C

Spec Gravity: