

THE PUROLITE CO. -- PUROLITE C-100 ION EXCHANGE RESIN -- 4610-01-116-0501

=====
Product Identification
=====

Product ID:PUROLITE C-100 ION EXCHANGE RESIN

MSDS Date:01/01/1991

FSC:4610

NIIN:01-116-0501

MSDS Number: BMTQZ

=== Responsible Party ===

Company Name:THE PUROLITE CO.

Address:150 MONUMENT ROAD

City:BALA CYNWYD

State:PA

ZIP:19004

Country:US

Info Phone Num:215-668-9090

Emergency Phone Num:21

5-668-9090

CAGE:MO962

=== Contractor Identification ===

Company Name:ION EXCHANGE PRODUCTS INC

Address:4834 S HALSTED

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-254-1300,312-847-7243

CAGE:23902

Company Name:PUROLITE COMPANY

Box:City:PHILADELPHIA

State:PA

ZIP:19134

CAGE:4300X

Company Name:THE PUROLITE CO.

Address:150 MONUMENT ROAD

Box:City:BALA CYNWYD

State:PA

ZIP:19004

Country:US

Phone:215-668-9090

CAGE:MO962

=====
Composition/Information on Ingredients
=====

In

Product Name:NON-HAZARDOUS FOR INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE GIVEN BY MANUF.

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT REPORTED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT, LIKE OTHER FOREIGN BODIES, MAY CAUSE MECHANICAL IRRITATION OF THE EYE.

Explanation of Carcinogenicity:NONE BY THE MANUFACTURER.

Effects of Overexposure:EYE: LIKE OTHER FOREIGN BODIES, PARTICLES MAY CAUSE MECHANICAL IRRITATION OF THE EYES.

Medical Cond Aggravated by Exposure:EYE CONTACT MAY CAUSE IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN IF IRRITATION PERSISTS.

=====
===== Fire Fighting Measures =====

Flash Point:NO FLASH POINT

Extinguishing Media:CA

RBN DIOXIDE, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WEAR MSHA/NIOSH APPROVED, PRESSURE DEMAND, SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:RESIN BEADS ON FLOOR MAY MECHANICALLY CAUSE FLOOR TO BE SLIPPER. USE CARE TO AVOID FALLS. SWEEP UP AND TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL.

=====
===== Handling and Storage =====

====

Handling and Storage Precautions:KEEP DRUMS AND PLASTIC BAGS SEALED TO PREVENT DRYING OR MOISTURE LOSS.

Other Precautions:STORE BELOW 49C (120F) AND ABOVE 0C (32F).

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:LOCAL EXHAUST: NORMAL ROOM VENTILATION

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE STATED BY MANUFACTURER.

Work Hygienic Practices:CLEANLINESS IS RECOMMENDED.

Supplemental Safety and Health

PH AQUE

OUS SLURRY 5 TO 7.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.32

pH:5-7

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER SPHERICAL BEAD WITHOUT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH CONCENTRATED NITRIC ACID, OR STRONG OXIDIZING AGENTS

Stability Condition to Avoid:AVOID TEMPERATURES >220C (428F)

Hazardous Decomposition Products:SO₂, SO₃, CO, CO₂, STYRENE MONOMER, DI-VINYL BENZENE

===== Disposal Considerations =====

Waste Disposal Methods:THIS MATERIAL CAN BE DISPOSED OF AS ORDINARY TRASH.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.