View NSN Online: https://aerobasegroup.com/nsn/6850-01-306-1382

MAGNAFLUX -- ZL-27A ZYGLO PENETRANT -- 6850-01-306-1382

Product ID:ZL-27A ZYGLO PENETRANT

MSDS Date:06/06/1991

FSC:6850

NIIN:01-306-1382

MSDS Number: BMWMC
=== Responsible Party ===
Company Name:MAGNAFLUX
Address:7300 W LAWRENCE AVE

City:CHICAGO

State:IL ZIP:60656 Country:US

Info Phone Num:708-867-8000

Emergency Phone Num:708-867-8000;800-424-9300(CHEMTREC)

Prep

arer's Name:BRUCE C. GRAHAM

CAGE:59042

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

Company Name: MAGNAFLUX

Address:7300 WEST LAWRENCE AVE

City:CHICAGO

State:IL ZIP:60656 Country:US

Phone:708-867-8000

CAGE:59042

======= Composition/Information on Ingredients ========


Ingred Name: MINERAL OIL, SLAB OIL; (WHITE MINERAL OIL). PEL/TLV: AS O

IL MIST. CAS:8042-47-5 RTECS #:PY8047000 Fraction by Wt: 40% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3, 10 STEL Ingred Name:PROPANE, 2-METHYL-; (ISOBUTANE) CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 30% ========== Hazards Identification ================ LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHAL: DIZZINESS, NAUSEA. SKIN: IRRITATION. DISSOLVES SKIN OILS. EYE: MILDLY IRRITATING. INGEST: GASTRIC UPSET. Explanation of Carcinogenicity: NOT RELEVANT. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: NONE. First Aid:INHAL: REMOVE TO FRESH AIR. SKIN: WASH OFF HANDS WITH SOAP AND WATER. USE SOOTHING LOTION, EYE: RINSE COPIOUSLY WITH WATER FOR AT LEAST 15 MIN. INGEST: SEE PHYS IF SEVERE. = Fire Fighting Measures =========== Flash Point Method: PMCC Flash Point:SUPP DATAY Lower Limits:1% **Upper Limits:6%** Extinguishing Media:CO*2, FOAM. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL

PROTECTIVE EQUIPMENT. KEEP CONTAINERS COOL WITH WATER SPRAY. DO NOT SPRAY WATER ON BURNING ZL-27A.

Unusual Fire/Explosion Hazard: AEROSOL CANS MAY BURST AT TEMPERATURES OVER 130F AND SPRAY OUT FLAMMABLE LIQUID.

======== Accidental Release Measures ==



Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:ON COMBUSTION, SMOKE, SOOT, OXIDES OF
CARBON AND NITROGEN.

======= Disposal Considerations ==========

activity Data ========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.