

GC ELECTRONICS -- 10-4302 -- 1560-00-012-0046

=====
Product Identification
=====

Product ID:10-4302
MSDS Date:07/07/1991
FSC:1560
NIIN:00-012-0046
MSDS Number: BMWNG
=== Responsible Party ===
Company Name:GC ELECTRONICS
Address:1801 MORGAN STREET
Box:1209
City:ROCKFORD
State:IL
ZIP:61105-1209
Country:US
Info Phone Num:815-968-9661
Emergency Phone Num:815-968-9661
CAGE:72653
=== Contractor Identif
ication ===
Company Name:GC THORSEN
Address:1801 MORGAN STREET
Box:City:ROCKFORD
State:IL
ZIP:61105
Country:US
Phone:815-968-9661
CAGE:72653

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 80%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identificati
=====

on =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE GIVEN
Effects of Overexposure:IRRITATES EYE AND RESPIRATORY
TRACT,DERMITITIS,HEADACHE,NAUSEA,DIZZINESS,PARALYSIS,DELERIUM.
Medical Cond Aggravated by Exposure:PERSONS WITH CNS DISEASES SHOULD
AVOID EXPOSURE

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT L
EAST 15MINUTES. SKIN:WASHWITH
SOAP AND WATER. INHALATION:FRESH AIR, OXYGEN, ARTIFICIAL
RESPIRATION IF NECESSARY. INGESTION: CONSULT A PHYSCIAN.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:22.0F,-5.6C
Lower Limits:1.8
Upper Limits:10.0
Extinguishing Media:CO2,CHEM FOAM, DRY CHEM.
Fire Fighting Procedures:TREAT AS FLAMMABLE LIQUID FIRE.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION-ABSORB WITH AN
INERT MATERIAL-STORE IN METAL CONTAINER FOR DISPOSAL. SOLVENT WILL
QUICKLY EVAPORATE FROM SMALL SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID HIGH TEMPERATURES AND IGINATION
SOURCES, STORE IN A COOL, WELL- VENTILATED AREA.
Other Precautions:AVOID INHALATION AND SKIN CONTACT

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:SCBA OR CHEMICAL CARTRIDGE RESPIRATOR
Ventilation:YES, MECHANICAL IF REQUIRED TO MEET TVL
Protective Gloves:BUTYL RUBBER
Eye Protection:CHEMICAL GOGGLES OR FACE SHIELD
Other Protective Equipment:APRON IF NECESSARY
Work Hygienic Practices:PRUDENT
Supplemental Safety and Health
NONE GIVEN

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:79.6F,26.4C
Vapor Pres:1.2
Vapor Density:2.41
Spec Gravity:0.87
Evaporation Rate
& Reference:< 1
Solubility in Water:NO
Appearance and Odor:TAN LIQUID-KEYTONE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:HEAT AND IGNITION SOURCES
Hazardous Decomposition Products:CO,CO2,CARBON COMBUSTION PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:LISCENSED INCINERATOR OR PER GOVERNMENT
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.