

TEXACO INC -- 68 -- 9150-00-023-5249

===== Product Identification =====

Product ID:68  
MSDS Date:10/29/1986  
FSC:9150  
NIIN:00-023-5249  
MSDS Number: BMWNV  
=== Responsible Party ===  
Company Name:TEXACO INC  
Box:509  
City:BEACON  
State:NY  
ZIP:12508-0509  
Country:US  
Info Phone Num:914-831-3400 EXT 204  
Emergency Phone Num:914-831-3400 EXT 204  
CAGE:7B131  
=== Contractor Identification ===  
Company Name:TEXACO  
INC  
Box:509  
City:BEACON  
State:NY  
ZIP:12508-0509  
Country:US  
Phone:914-831-3400  
CAGE:7B131

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY  
PARAFFINIC  
CAS:64742-65-0  
RTECS #:PY8038500  
Fraction by Wt: 65-79.9%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:HYDROTREATED C25 BRIGHT STOCK BASED LUBRICATING OIL  
CAS:72623-83-7  
Fraction by Wt: 20-34.9%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN AND EYES; MILDILY IRRITATING.  
INHALATION IRRITATION TO RESPIRATORY TRACT.  
Effects of Overexposure:NA  
Medical Cond Aggravated by Exposure:NONE KNOWN

=====  
===== First Aid Measures =====

First Aid:EYES;FLUSH WITH PLENTY OF WATER. SKIN; WASH WITH SOAP AND WATER.

=====  
===== Fire Fighting Measures =====

Flash Point:ND  
Lower Limits:ND  
Upper Limits:ND  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL FOAM, OR CARBON DIOXIDE.  
USE WATER TO COOL FIRE EXPOSED CONTAINERS.  
Fire Fighting Procedures:WATER OR FAOM MAY CAUSE FROTHING. IF A SPILL OR LEAK HAS NOT IGNITED USE WATER SPRAY TO DISPERSE VAPORS.  
Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spi  
II Release Procedures:CONTAIN SPILL IF POSSIBLE, WIPE UP OR ABSORB EXCESS ON SUITABLE MATERIAL AND SHOVEL UP.  
Neutralizing Agent:NA

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT MINIMUM FEASIBLE TEMPERATURES, EXPOSURE TO HIGH TEMPERATURES SHOULD BE AVOIDED.  
Other Precautions:NA

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED  
Ventilation:LOCAL  
Protective Gloves:PER

SONAL CLEANINESS

Eye Protection:GOGGLES OR FACE SHIELD OPTIONAL

Other Protective Equipment:NA

Work Hygienic Practices:CLEAN EXPOSE SKIN SEVERAL TIMES A DAY WITH SOAP AND WATER, LAUNDER SOILED WORK CLOTHES AT LEAST WEEKLY.

Supplemental Safety and Health

NA

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:ND

Vapor Pres:ND

Vapor Density:ND

Spec Gravity:0.8857

Evaporation Rate & Reference:ND

Solubility in Water:ND

Appearance and Odor:VERY DAR

K RED LIQUID

Percent Volatiles by Volume:ND

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE GIVEN

Stability Condition to Avoid:NONE GIVEN

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, ALDEHYDES AND KEYTONES.

===== Disposal Considerations =====

Waste Disposal Methods:IF DETERMINED HAZARDOUS IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.