

POWER-SONIC CORP -- POWER SONIC RECHARGEABLE BATTERIES -- 6140-01-225-5935
===== Product Identification =====

Product ID:POWER SONIC RECHARGEABLE BATTERIES

MSDS Date:01/14/1990

FSC:6140

NIIN:01-225-5935

MSDS Number: BMXCN

=== Responsible Party ===

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Info Phone Num:415-364-5001

Emergenc

y Phone Num:415-364-5001

CAGE:56309

=== Contractor Identification ===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Phone:650-364-5001

CAGE:56309

===== Composition/Information on Ingredients =====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fract

ion by Wt: 17%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: BURNS, OR EYE DAMAGE FROM
SULFURIC ACID ELECTROLYTE. ILLNESS FROM SULFUR OXIDE FUMES.
CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of

Carcinogenicity:THIS PRODUCTS INGREDIENTS ARE NOT FOUND
IN OSHA, NTP OR IARC LIST'S OF CARCINOGENS.

Effects of Overexposure:INHALE: NASAL AND RESPIRATORY IRRITATION FROM
SULFUR DIOXIDE FUMES. EYE OR SKIN: BURNS, SKIN IRRITATION AND EYE
DAMAGE. INGESTA: STOMACH IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER AND OBTAIN MEDICAL ADVICE. SKIN-FLUSH
WI
TH WATER AND OBTAIN MEDICAL ADVICE. INHALE-DISCONNECT BATTERIES
AND VENTILATE AREA. INGEST-DRINK LARGE QUANTITIES OF WATER OR MILK,
FOLLOWE D MY MILK OF MAGNESIA. CONTACT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:DIRECT FLAME

Extinguishing Media:USE WATER SPRAY, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:THE NON-CONDUCTIVE POLYSTRENE CASING IS NON-
FLAMMABLE PER UL94 RATING VE-0 OR VE-1.

Unusual Fire/Explosion Hazard:KEEP AWAY
FROM OPEN FLAMES AND SPARKS.

IMPROPER CHARGING AND IGNITION OF RESULTING GASES CAN CAUSE
EXPLOSION, PARTICULARY IN GAS TIGHT ENCLOSURES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:THE ELECTROLYTE IS IMMOBILIZED AND COMPLETELY
SECURED WITHIN THE BATTERY CASE. IF CASE IS CRACKED AVOID CONTACT
WITH ELECTROYLTY, WRAP TIGHTLY IN POLYETHYLENE BAGS.

=====
===== Handling and Storage =====

Handling and Stor

age Precautions:PROTECT AGAINST CRACKING OF CASE
MATERIAL. ADHERE TO PROPER CHARGING PROCEDURES.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Supplemental Safety and Health
NONE

=====
Physical/Chemical Properties
=====

HCC:N1

Appearance and Odor:RECTANGULAR/SQUARE IN SHAPE-ORANGE IN COLOR-NO
ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

SO

LVENTS MAY DISSOLVE CASE MATERIAL.

Hazardous Decomposition Products:SEVERE OVERCHARGING AND OVERHEATING
MAY CAUSE HYDROGEN, OXYGEN AND SULFUR DIOXIDE FUMES.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE WITH AUTOMOTIVE SCRAP BATTERIES. DO NOT
INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of Amer
ica in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.