

=====
Product Identification
=====

Product ID:POWER SONIC RECHARGEABLE BATTERIES

MSDS Date:01/14/1990

FSC:6140

NIIN:01-225-5935

MSDS Number: BMXCN

=== Responsible Party ===

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Info Phone Num:415-364-5001

Emergency Phone Num:415-364-5001

CAGE:56309

=== Contractor Identification

===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Phone:650-364-5001

CAGE:56309

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 17%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1 MG/M3

A

CGIH TLV:1 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: BURNS, OR EYE DAMAGE FROM
SULFURIC ACID ELECTROLYTE. ILLNESS FROM SULFUR OXIDE FUMES.
CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:THIS PRODUCTS INGREDIENTS ARE NOT FOUND
IN O

SHA, NTP OR IARC LIST'S OF CARCINOGENS.

Effects of Overexposure:INHALE: NASAL AND RESPIRATORY IRRITATION FROM
SULFUR DIOXIDE FUMES. EYE OR SKIN: BURNS, SKIN IRRITATION AND EYE
DAMAGE. INGESTA: STOMACH IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====
=====

First Aid:EYE-FLUSH WITH WATER AND OBTAIN MEDICAL ADVICE. SKIN-FLUSH
WITH WATER AND OBTAIN MEDICAL ADVICE. INHALE-DISCONNECT BATTERIES

AND VENTILATE AREA. INGEST-DRINK LARGE QUANTITIES OF WATER OR MILK,
FOLLOWE D MY MILK OF MAGNESIA. CONTACT PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point:DIRECT FLAME

Extinguishing Media:USE WATER SPRAY, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:THE NON-CONDUCTIVE POLYSTRENE CASING IS NON-
FLAMMABLE PER UL94 RATING VE-0 OR VE-1.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAMES AND SPARKS.
IMPROPER CHARGING AND IGNITION O

F RESULTING GASES CAN CAUSE

EXPLOSION, PARTICULARY IN GAS TIGHT ENCLOSURES.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:THE ELECTROLYTE IS IMMOBILIZED AND COMPLETELY
SECURED WITHIN THE BATTERY CASE. IF CASE IS CRACKED AVOID CONTACT
WITH ELECTROYLTY, WRAP TIGHTLY IN POLYETHYLENE BAGS.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:PROTECT AGAINST CRACKING OF CASE
MATERIAL. AD

HERE TO PROPER CHARGING PROCEDURES.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:RECTANGULAR/SQUARE IN SHAPE-ORANGE IN COLOR-NO
ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

SOLVENTS MAY DISSOLVE CASE MATERIAL.

Hazardous Decomposition Products:

SEVERE OVERCHARGING AND OVERHEATING

MAY CAUSE HYDROGEN, OXYGEN AND SULFUR DIOXIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE WITH AUTOMOTIVE SCRAP BATTERIES. DO NOT
INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this
information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.