

FARWEST PAINT MANUFACTURING CO -- A-A-1558 CLASS 1, 32247 ORANGE STENCIL PAIN --  
8010-00-285-4929

===== Product Identification =====

Product ID:A-A-1558 CLASS 1, 32247 ORANGE STENCIL PAIN

MSDS Date:09/27/1989

FSC:8010

NIIN:00-285-4929

MSDS Number: BMXGM

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD STREET

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

CAGE:2F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:2F266

===== Composition/Information on Ingredients =====

Ingred Name:VM & P NAPTHA, ALIPHATIC HYDROCARBONS

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 22.6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:300 PPM

Ingred Nam

e:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 3.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE  
IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PR  
OLONGED OR  
REPEATED CONTACT. SOME REPORTS HAVE ASSOCIATED REPEATED & PROLONGED  
OCCUPATIONAL OVEREXPOSURE TO SOLVENT WITH PERMANENT BRAIN AND  
NERVOUS SYSTEM DAMAGE. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.  
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN  
CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY ACGIH, OSHA,  
NTP, IARC.  
Effects of Overexposure:INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR  
SPRAY MISTS CAN RESULT IN HEADACHE, DIZZINESS, NAUSEA AND LOSS  
OF  
CONSCIOUSNESS.  
Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH  
SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/SOAP & WATER. REMOVE & WASH  
CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH W/WATER 15 MIN, &  
GET MED AID. INGESTION: IF INGESTED, DON'T INDUCE VOMITING, KEEP  
PERSON WARM, QUIET, & GET MED AID. ASPIRATION OF MATERIAL INTO  
LUNGS CAN CAUSE CHEMICAL PNEUMONI  
TIS WHICH CAN BE FATAL. INHAL:  
REMOVE TO FRESH AIR IMMED. IF RESPIRATORY SYMPTOMS DEVELOP, GET MED  
AID AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Point:50.0F,10.0C  
Lower Limits:1.0%  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH A FULL  
FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE  
MODE.  
Unusual Fire/Explosion Hazard:NEVER USE NEAR OR AROUND WELDERS OR  
C

UTTING TORCHES. DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. VENT AREA. ABSORB SPILL W/ABSORBENT MAT'L (SAWDUST, VERMICULITE, SAND). PLACE MAT'L INTO CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TO PREVENT THIS MAT'L FROM ENTERING WATER SYS TEMS/SEWERS. WEAR PROTECT EQUIP DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:GROUND HANDLING EQUIPMENT TO PREVENT SPARKS. AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MISTS. KEEP AWAY FROM HEAT/IGNIT SOURCE.

Other Precautions:MAT'L MAY CAUSE SENSITIZATION. DON'T GET IN EYES, ON SKIN/CLOTHING. DON'T ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DON'T WELD ON FULL/EMPTY CNTNRS. KEEP CNTNRS CLSD WHEN NOT IN USE & PROPERLY LABL ED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS OR SPRAY MISTS WHEN TLV/PEL EXCEEDED.

Ventilation:GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP BELOW TLV/PEL.

Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATIONS & SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:228 TO 282F

Vapor Pres:22.0 @ 20C

Vapor Density:> AIR

Spec Gravity:11.60 LBS/GAL

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:ORANGE MEDIUM VISCOUS LIQUID WITH A MILD SWEET AROMATIC ODOR.

Percent Volatiles by Volu

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT SPARKS & OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLSD CNTNRS WILL GENERATE HYDROGEN GAS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT MAT'L & CNTNR AS HAZARDOUS WASTE BASED ON IGNIT CHARACTERISTIC AS DEFINED UNDER FED RCRA REGS (40 CFR 261). MAT'L DISPOSAL/CNTNR REQUIRES COMPLIANCE W/APPLIC LABELING/PACKAGING/ RECORDKEEPING ST DS. DISPOSE IN ACCORD W/LOCAL, STATE, FED AGENCIES

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.