

CHEMRAY COATING CORP -- PIGMENTED POLYMER GRAY 16376 -- 8010-00-664-7084
===== Product Identification =====

Product ID:PIGMENTED POLYMER GRAY 16376

MSDS Date:11/13/1989

FSC:8010

NIIN:00-664-7084

MSDS Number: BMXHW

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:201-

245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM SOLVENT, MS 66

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 21%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

===== Hazards Identific

ation =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:OVEREXPOSURE: NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION.
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MIN OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND
WATER. INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR,
CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:100F,38C
Autoignition Temp:Autoignition Temp Text:473F
Lower Limits:0.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPOR OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. KEEP FROM HEAT, SPARKS &
FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENT AREA
(OPEN WINDOW, DOOR) IF LRG SPILL KEEP PRODUCT FROM ENTERING SEWERS
& WATERCOURSES BY DIKING.
ADVISE AUTHORITIES IF PRODUCT ENTERED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP
IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT AND
EXTREME TEMPERATURES--HOT OR COLD.
Other Precautions:AVOID EYE, SKIN CONTACT. INHALATION INGESTION OF
MISTS, SPRAY OR VAPORS. AVOID BREATHING, SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respi

ratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATORY IN CONFINED AREA.

Ventilation:LOCAL EXHAUST--FACE VELOCITY 60FPM. SPECIAL--USE ONLY WITH
ADEQUATE VENTILATION. MECHANICAL--USE EXPLOSION PROOF EQUIP.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boi

ling Pt:B.P. Text:308F,153C

Melt/Freeze Pt:M.P/F.P Text:0F,-18C

Decomp Temp:Decomp Text:600F,316C

Vapor Pres: