

MOBIL OIL CORP BEAUMONT REFINERY -- MOBIL MULTI-PURPOSE ATF -- 9150-01-092-9755

===== Product Identification =====

Product ID:MOBIL MULTI-PURPOSE ATF

MSDS Date:11/12/1991

FSC:9150

NIIN:01-092-9755

MSDS Number: BMZJY

=== Responsible Party ===

Company Name:MOBIL OIL CORP BEAUMONT REFINERY

Address:INTERSTATE 10

Box:3311

City:BEAUMONT

State:TX

ZIP:77704

Country:US

Info Phone Num:800-662-4525

Emerge

ncy Phone Num:609-737-4411

CAGE:LO311

=== Contractor Identification ===

Company Name:MOBIL OIL CORP BEAUMONT REFINERY

Address:INTERSTATE 10

Box:3311

City:BEAUMONT

State:TX

ZIP:77704

Country:US

Phone:800-662-4525

CAGE:LO311

Company Name:MOBIL OIL CORPORATION

Address:BEAUMONT REFINERY INTERSTATE 10

Box:3311

City:BEAUMONT

State:TX

ZIP:77704

Country:US

Phone:609-737-4411/800-424-9300(CHEMTREC)

CAGE:19135

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Coun

try:US
Phone:504-366-4542
CAGE:0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

LD50 LC50 Mixture:5.00 MG/M3 SUGGESTED FOR OIL MIST

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazar

ds Acute and Chronic:THIS MATERIAL IS EXPECTED TO BE NON-IRRITATING AND NONTOXIC.

Effects of Overexposure:NOT EXPECTED TO BE A PROBLEM.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN. SKIN: WASH CONTACT AREAS WITH SOAP AND WATER.

INHALATION: REMOVE FROM FURTHER EXPOSURE. IF RESPIRATORY IRRITATION, DIZZI

N ESS, NAUSEA, OR UNCONSCIOUSNESS OCCURS,SEEK

IMMEDIATE MEDICAL ASSISTANCE AND CALL A PHYSICIAN. IF BREATHING HAS STOPPED, USE MOUTH TO MOUTH RESUSCITATION. INGESTION:NONE NORMALLY

REQUIRED.

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:>350F,>177C

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

Fire Fighting Procedures:WATER OR FOAM AMY CAUSE FROTHING. USE WATER TO

KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

Unusual Fire/Explosion Hazard:FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED AREAS. PREVENT RUNOFF FORM FIRE CONTROL OR DILUTION FORM ENTERING STREAMS.

===== Accidental Release Measures =====

Spill Release Procedures:REPORT SPILLS AS REQUIRED TO APPROPRIATE AUTHORITIES. U.S. COAST GUARD REGULATIONS REQUIRE IMMEDIATE REPORTING OF SPILLS THAT COULD REACH ANY WATERWAY INCLUDING INTERMITTENT DRY CREEKS. REPORT SPILL TO COAST GUARD TOLL FREE NUMBER 800-424-8802.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTSS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:USE IN WELL VENTILATED AREA.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:NORMAL INDUSTRIAL EYE PROTECTION.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING THIS MATERIAL.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: