View NSN Online: https://aerobasegroup.com/nsn/8010-01-200-2637

ASHLAND CHEMICAL CO IC AND S DIV -- SOLVENT BLEND T 81772 TYPE 2 REV

8010-01-200-2637

============= Product Identification =================

Product ID:SOLVENT BLEND T 81772 TYPE 2 REV

MSDS Date: 10/03/1990

FSC:8010

NIIN:01-200-2637

MSDS Number: BMZLV === Responsible Party ===

Company Name: ASHLAND CHEMICAL CO IC AND S DIV

Address:5200 BLAZER PKY

Box:2219 City:DUBLIN State:OH ZIP:43017 Country:US

Info Phone Num :614-889-3844

Emergency Phone Num:614-889-3844

**CAGE:5A188** 

=== Contractor Identification ===

Company Name: ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH ZIP:43017 Country:US

Phone:614-889-4505

CAGE:5A188

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ISOBUTYL KETONE (SARA 313)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 35%

Other REC Limits:NIOSH 50 PPM TWA

OSHA PEL:100 PPM/75 STEL ACGIH TLV:50 PPM/75 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000 Fraction by Wt: 65%

Other REC Limits: NONE SPECIFIED

**OSHA PEL:100 PPM** 

ACGIH TLV:100 PPM/150 PPM STEL

=========== Hazards Identification ==========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: EYES: IRRITATION. SKIN: MODERATE

IRRITATION, DEFATTING, DERMA TITIS. BREATHING: NASAL, RESP

IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS, DEATH. SWALLOWING: GASTROINTESTINAL IRRITATION. OVEREXPOSURE TO M ATERIAL (OR COMPONENTS) HAS BEEN FOUND TO CAUSE (LAB ANIMAL) FOLLOWING: LIVER ABNORMALITIES, KIDNEY, LUNG, BRAIN DAMAGE.

Effects of Overexposure:EYES: REDNESS, TEARING. BREATHING: CENTRAL NERVOUS SYSTEM EFFECTS: WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS. SWALLOWING NAUSEA, VOMITING, DIARRHEA.

==== First Aid Measures ==========

First Aid:SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTH. EYES: FLUSH W/LRG AMT WATER, LIFT EYELIDS OCCASION, GET MED ATTN. INGEST: DON'T INDUCE VOMIT, KEEP PERSON WARM, QUIET, GET MED ATTN. ASPIRATION (MATERIA L INTO LUNGS--VOMIT) CAN CAUSE CHEM PNEUMONITIS (CAN BE FATAL). INHAL: REMOVE TO FRESH AIR. IF BREATHING DIFFICULT, ADMIN OXYGEN. IF BREATHING STOPPED GIVE ARTIF RESP. KEEP WARM, QUIET, GET MED AID.

=========

====== Fire Fighting Measures =========

Flash Point Method:TCC Flash Point:55.0 TO 65.0F

Lower Limits: 1.4

Extinguishing Media:REGULAR FOAM, OR CARBON DIOXIDE OR DRY CHEMICAL. @ 760.00 MM HG. LOWEST VALUE OF COMPONENT IS LISTED FOR MIX.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES. @ 68F. HIGHEST VALUE.

Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR, MAY T

ALONG GROUND OR MOVED BY VENT & IGNITED BY PILOT LIGHT, FLAME, SPARK, HEATER, SMOKING, ELEC MOTOR, STATIC, IGNIT SOURCE.
======== Accidental Release Measures ==========
Spill Release Procedures:SMALL: ABSORB LIQ ON ABSORBENT. LARGE: ELIMIN IGNIT SOURCE. EVAC UNPROTECTED. STOP SPILL. DIKE SPILL, PUMP TO SALV TANK. REMAINING MAY BE TAKEN UP ON ABSORB. SHOVEL INTO CNTNRS. PREVENT RUNOFF TO SEWE R/STREAM/WATER BODY. NOTIFY AUTHORITIESOF SPILL.
=== ==================================
Handling and Storage Precautions:CNTNRS OF MAT'L MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CNTNRS RETAIN PRODUCT RESIDUES, OBSERVE ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF TLV/PEL OF PRODUCT/COMPNENT EXCEEDED, NIOSH/ MSHA AIR SUPPLIED RSPRTR ADVISED IN ABSENCE OF ENVIRONMENT CONTROL OSHA REGS PERMIT NIOSH/MSHA RSPRTRS (NEG PRESS TYPE) UNDER SPECIFIED COND. IMPLEMENT ENGINEERING/ADMINISTRATION CONTROLS. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL/LOCAL EXHAUST) VENT TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:WEAR REISSTANT GLOVES. Eye Protection:CHEM SPLASH GOGGLES, SAFETY GLASSES. Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS. Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safet y and Health
========== Physical/Chemical Properties ===========
HCC:F2 Boiling Pt:B.P. Text:237F,114C Vapor Pres:16. @68F Spec Gravity:

RAVEL