

Product ID:9156, BENZENE MSDS Date:07/30/1986 FSC:6810 NIIN:00-978-1878 MSDS Number: BNBSH === Responsible Party === Company Name: J T BAKER INC Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865-2219 Country:US Info Phone Num:800-582-2537 Emergency Phone Num:908-859-2151;800-424-9300(CHEMTREC) CAGE :DO803 === Contractor Identification === Company Name: J T BAKER INC Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:1-800-582-2537 CAGE:DO803 Company Name: MALLINCKRODT BAKER, INC. Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:800-582-2537 CAGE:70829

Ingred Name:BENZENE; (BENZOL) (SARA III) CAS:71-43-2 RTECS #:CY1400000 Fraction by Wt: 90-100% Other RE C Limits:STEL: 25 PPM (MFR) OSHA PEL:1 PPM;5 PPM STEL ACGIH TLV:10 PPM EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:LD50: (ORAL, RAT) 4894 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE: INHALATION OF VAPORS MAY CAUSE HEADACHE, NAUSEA, DIZZINESS, FATIGUE AND WEAKNESS IN ARMS/LEGS. CHRONIC: CHRONI
C EFFECTS OF OVEREXPOSURE MAY INCLUDE KIDNEY &/OR
LIVER DAMAGE. IRREVERSIBLE INJURY TO BLOOD FORMING TISSUE MAY
RESULT FROM CHRONIC LOW LEVEL EXPOSURE. INHALATION OF BENZENE MAY
CAUSE APLASTIC ANEMIA.
Explanation of Carcinogenicity:BENZENE: GROUP 1 (IARC), GROUP 1 (NTP), ACGIH GRP A2, OSHA REGULATED.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE IDENTIFIED.

First Aid:CAL

L MD. -- INGEST: DO NOT INDUCE VOMIT. IF CONSCIOUS, GIVE WATER, MILK OR MILK OF MAGNESIA. INHAL: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. EYES/SKIN: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.

Flash Point Method:CC Flash Point:12F,-11C Lower Limits:1% Upper Limits:7% Extinguishing Media:USE ALCOHOL FOAM, DRY CHEMICAL OR CARBON DIOXIDE. (WATER MAY BE INEFFECTIVE).

Fire Fighting Procedures:WEAR NIÓSH/MSHA APPROVED SCBA & FULL PROT EQUIP . MOVE CONTRS FROM FIRE AREA IF POSSIBLE WITHOUT RISK. USE WATER TO KEEP FIRE-EXPOSED CONTRS COOL.

Unusual Fire/Explosion Hazard: VAPORS MAY FLOW ALONG SURFACES TO DISTANT IGNITION SOURCES & FLASH BACK. CLOSED CONTRS EXPOSED TO HEAT MAY EXPLODE. CONTACT W/STRONG OXIDIZERS MAY CAUSE FIRE.

Spill Relea

se Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. SHUT OFF IGNIT SOURCES; NO FLARES/SMKG/FLAMES IN AREA. STOP LEAK IF POSSIBLE W/O RISK. USE WATER SPRAY TO REDUCE VAPS. TAKE UP W/SAND/OTHER NON-COMBUST A BSORB MATL (J. T. BAKER SOLUSORB (SUPP DATA)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL, DRY, WELL-VENTILAT

ED, FLAMMABLE LIQUID STORAGE AREA OR CABINET.

Other Precautions: POISON! DANGER! EXTREMELY FLAMMABLE. HARMFUL IF SWALLOWED/INHALED/ABSORBED THRU SKIN. CAUTION: CONTAINS BENZENE, CANCER HAZARD. KEEP AWAY FROM HEAT, SPARKS, FLAME. AVOID CONTACT W/EYES, SKIN CLTHG. AV OID BREATHING VAP. USE W/ADEQ VENT.

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION REQUIRED IF AIRBORNE CONCENTRATION EXCEEDS

TLV. AT CONCENTRATIONS

ABOVE 10 PPM, A NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS IS ADVISED.

Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves: IMPERVIOUS GLOVES .

Eye Protection: CHEM WORK GOGG/FULL LENGTH FSHLD .

Other Protective Equipment:UNIFORM, PROTECTIVE SUIT ARE RECOMMENDED.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

SPILL PROC: SOLVENT ABSORBENT IS RECOMMENDED) AND PLACE INT O CONTAINER

FOR LATER DISPOSAL. FLUSH AREA WITH WATER.

Boiling Pt:B.P. Text:176F,80C Melt/Freeze Pt:M.P/F.P Text:43.0F,6.1C Vapor Pres:74.6 Vapor Density:2.8 Spec Gravity:0.88 (H*2O=1) Solubility in Water:NEGLIGIBLE (