

TACC INTERNATIONAL CORP. -- XJD 0107B LAGGING COMPOUND -- 8030-01-008-0836

=====
Product Identification
=====

Product ID:XJD 0107B LAGGING COMPOUND

MSDS Date:01/01/1991

FSC:8030

NIIN:01-008-0836

Kit Part:Y

MSDS Number: BNCHK

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878

-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazar

ds Acute and Chronic:INHALATION: AVOID BREATHING VAPORS IN CONTAINER HEADSPACE. EYES: ACUTE & CHRONIC: IRRITANT. SKIN: MAY BE IRRITATING TO SKIN. CHRONIC OVEREXPOSURE MAY LEAD TO SKIN SENSITIZATION. INGESTION: HARMFUL OR FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: OBTAIN FRESH AIR. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. APPLY LOTION IF NECESSARY. INGESTION: CALL POISON CENTER IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY.
Fire Fighting Procedures:DO NOT SPRAY A SOLID STREAM OF WATER OR FOAM DIRECTLY INTO A POOL OF HOT BURNING LIQUID; THIS MAY CAUSE FROTHING. USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMPERATURES MAY CAUSE INSTABILITY. DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL QUANTITIES MAY BE ABSORBED WITH APPROPRIATE ABSORBENT. FOR LARGE SPILLS SEE SECTIONS ON FIRE HAZARD, SPECIAL PROTECTIONS AND SPECIAL PRECAUTIONS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT 60-95F OUT OF DIRECT SUN, IN DRY AREA. USE ADEQUATE VENT TO AVOID BREATHING VAPOR WHEN COVER IS REMOVED; SEE SECTION ON HEALTH HAZARDS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPORS EXCEED TLV USE CONTAINED ORGANIC MASK, NIOSH APPROVED.
Ventilation:LOCAL EXHAUST: SUFFICIENT TO KEEP WORKROOM CONCENTRATIONS BELOW TLV.
Protective Gloves:CHEMICAL RESISTANT GLOVES.
Eye Protection:SAFETY GLASSES OR FACE SHIELD.
Other Protective Equipment:BARRIER CREAM FOR SENSITIVE SKIN.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

=====

Spec Gravity:1.2 (WATER=1)
Evaporation Rate & Reference: