

COPPS INDUSTRIES, INC. -- MV-F TAN PN-A-012 EPOXY RESIN -- 8040-00-726-3567

=====
Product Identification
=====

Product ID: MV-F TAN PN-A-012 EPOXY RESIN

MSDS Date: 03/19/1990

FSC: 8040

NIIN: 00-726-3567

Kit Part: Y

MSDS Number: BNKQS

=== Responsible Party ===

Company Name: COPPS INDUSTRIES, INC.

Address: N 90 W 14683 COMMERCE DR

Box: 844

City: MENOMONEE FALLS

State: WI

ZIP: 53051

Country: US

Info Phone Num: 4

14-251-3825

Emergency Phone Num: 414-251-3825

CAGE: COPPS

=== Contractor Identification ===

Company Name: COPPS INDUSTRIES, INC.

Address: N 90 W 14683 COMMERCE DR

Box: 844

City: MENOMONEE FALLS

State: WI

ZIP: 53051

Country: US

Phone: 414-251-3825

CAGE: COPPS

=====
Composition/Information on Ingredients
=====

Ingred Name: EPOXY RESIN

CAS: 25085-99-8

Fraction by Wt: >1%

Other REC Limits: NONE SPECIFIED

Ingred Name: EPOXY RESIN DILUENT (N-BUTYL GLYCIDYL ETHER)

CAS: 2426-08-6

RTECS #: TX4200000

Fraction by Wt: >1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM; 9293

Ingred Name:THIXOTROPE (SILICA, AMORPHOUS)
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: >1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:20 PPM T DUST
ACGIH TLV:10 PPM T DUST

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES OSHA:YES
Explanation of Carcinogenicity:AMPORHOUS SI
LICA IS LISTED AS A
CARCINOGEN.
Effects of Overexposure:EYES: MAY CAUSE SLIGHT IRRITATION. SKIN: MAY
CAUSE SLIGHT IRRITATION, A MODERATE SENSITIZER. INHALATION: MAY
CAUSE DIZZINESS AND RESPIRATORY IRRITATION. INGESTION: MAY BE
IRRITATING TO INTERNAL TISSUE S.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. OBTAIN MEDICAL
ATTENTION. SKIN: WASH WITH SOAP AND WATER; REMOVE AND WASH
CONTAMINATED CLOTHING.
INHALATION: REMOVE TO FRESH AIR; OBTAIN
MEDICAL ATTENTION. INGESTION: INDUCE VOMITING; OBTAIN MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====
=====

Flash Point:>200F,>93C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:FOR MAJOR FIRES, FULL PROTECTIVE EQUIPMENT
INCLUDING BREATHING APPARATUS IS RECOMMENDED. HAZARDOUS COMBUSTION
PRODUCTS MAY BE PRESENT.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:SPREAD ABSORBENT MATERIAL OVER AREA; WIPE OR SCRAPE UP MATERIAL. WASH WITH SOAP AND WATER; PREVENT WASHINGS FROM ENTERING SEWERS OR WATERWAYS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL (60 - 80F), DRY PLACE.
Other Precautions:REMOVE CONTAMINATED CLOTHING AND GEAR. DECONTAMINATE.
DESTROY LEATHER OR ANY ARTICLES WHICH CANNOT BE DECONTAMINATED.
CONTACT LENSES SHOULD NOT BE WORN WHILE USING THIS PRODUCT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY UNDER MOST OPERATING CONDITIONS.
NIOSH APPROVED ORGANIC VAPOR RESP SHOULD BE USED IN CONFINED AREAS/
WHEN CONDITIONS CAUSE HIGH VAPOR CONCENTRATIONS. IF THE PERCENT OXYGEN IS BELOW NORMAL , USE SELF-CONTAINED BREATHING APPARATUS

Ventilation:FORCED LOCAL EXHAUST IS RECOMMENDED IN CONFINED AREAS.

Protective Gloves:CHEMICAL RESISTANT GLOVES RECOMMENDED.

Eye

Protection:CHEMICAL SAFETY GOGGLES RECOMMENDED.

Other Protective Equipment:EYE WASH STATIONS AND SAFETY SHOWERS SHOULD BE EASILY ACCESSIBLE. CLEAN BODY COVERING CLOTHING SHOULD BE UTILIZED.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>200F

Vapor Density:> THAN AIR

Spec Gravity:1.4

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIQUID WITH SWEET ODOR.

Percent Volatiles by Volume:0

=====
=====

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH ACIDS AND STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE NORMALLY.

Hazardous Decomposition Products:NONE NORMALLY. INCOMPLETE COMBUSTION MAY FORM ALDEHYDES, NITROUS OXIDES CO, CO2.

Conditions to Avoid Polymerization:CONTACT WITH ACIDS AND STRONG OXIDANTS; CONTACT WITH EPOXY HARDNERS UNDER UNCONTROLLED CONDITIONS.

=====
===== Disposal Co

nsiderations =====

Waste Disposal Methods:INCINERATE OR BURY IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should
seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.