

WORLD WIDE WELDING INC. -- AIR CARBON ARC ELECTRODES -- 3439-00-870-9934

=====
Product Identification
=====

Product ID: AIR CARBON ARC ELECTRODES

MSDS Date: 01/01/1991

FSC: 3439

NIIN: 00-870-9934

MSDS Number: BNNGB

=== Responsible Party ===

Company Name: WORLD WIDE WELDING INC.

Address: 3300-G WOODPARK BLVD

Box: 217006

City: CHARLOTTE

State: NC

ZIP: 28206

Country: US

Info Phone Num: 704-596-0123

Emergency Ph

one Num: 704-596-0123

CAGE: 59754

=== Contractor Identification ===

Company Name: WORLD WIDE WELDING INC

Address: 3300-S WOODPARK BLVD

Box: 217006

City: CHARLOTTE

State: NC

ZIP: 28221

Country: US

Phone: 704-596-0123

CAGE: 59754

=====
Composition/Information on Ingredients
=====

Ingred Name: GRAPHITE, NATURAL

CAS: 7782-42-5

RTECS #: MD9659600

Fraction by Wt: 20-80%

Other REC Limits: NONE SPECIFIED

OSHA PEL: 15 MPPCF RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9293

Ingred Name: GRAPHITE, SYNTHETIC

CAS: 7440

-44-0
RTECS #:FF5250100
Fraction by Wt: 20-80%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 10-30%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR WELDING FUMES IS 5 MG/M3
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:BRONCHITIS, LUNG DEPOSITS, AND TISSUE
DAMAGE WHICH MAY BE IRREVERSIBLE. EXPOSURE TO ULTRA-VIOLET ARC RAYS
CAN RESULT IN KERATOCONJUNCTIVITIS, CAUSING INFLAMMATION, BLURRED
VISION, HEADACHE "SUNBURN".
Effects of Overexposure:BREATHING DI
FFICULTY, HEADACHE, NAUSEA, DRYNESS
OR IRRITATION OF NOSE, THROAT AND EYES. BURNING SENSATION OF EYES.
UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT,
GIVE OXYGEN. IF NOT BREATHING, GIVE CPR. IF NO DETECTABLE PULSE,

GIVE HEART MASSAGE. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INGESTION: SEEK MEDICAL ATTENTION. TREAT UV EXPOSURE SIMILAR TO SEVERE SUNBURN.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED

CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:ARCS AND SPARKS CAN IGNITE COMBUSTIBLE MATERIALS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DISPOSAL CONTAINER. AVOID INHALATION AND SKIN EXPOSURE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP P BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH, ARM PROTECTOR, APRON, HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE MEASURES

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING, SMOKING OR USING SANITARY FACILITIES.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INS

OLUBLE.

Appearance and Odor:CUTTING ELECTRODE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:FUMES OF METALS AND METAL OXIDES FROM
ELECTRODE AND BASE METAL, CARBON MONOXIDE, CARBON DIOXIDE, OZONE,
NITROGEN OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL OFFICER.

DISPOSE OF FUMES, FLUX OR WELD GRINDING RESIDUE FROM THE WORK AREA
OR FROM FILTERS IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL
ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.