

KOCH MATERIALS COMPANY -- PRODUCT 9020, COMPONENT A -- 8030-00-823-7972

=====  
Product Identification  
=====

Product ID:PRODUCT 9020, COMPONENT A

MSDS Date:02/13/1992

FSC:8030

NIIN:00-823-7972

Kit Part:Y

MSDS Number: BNPRW

=== Responsible Party ===

Company Name:KOCH MATERIALS COMPANY

Address:HWY 66 EAST

Box:510

City:STROUD

State:OK

ZIP:74079

Country:US

Info Phone Num:800-654-9182/918-968-3654 (FAX)

Emergency Phone Num:916-832-6777/800-424-9300 CHEMTREC

Preparer's Name:CARL L HARVATH

CAGE:0TAB0

=== Contractor Identification ===

Company Name:KOCH MATERIALS CO COATINGS/SEALANTS DIV

Box:2338

City:STROUD

State:OK

ZIP:74079-0519

Country:US

Phone:918-968-3541

CAGE:0TAB0

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SODIUM BICHROMATE (SARA III)

CAS:10588-01-9

RTECS #:HX7700000

Fraction by Wt: 24%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0

.5 MG/M3  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:CALCIUM CARBONATE  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 41%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10 MG/M3  
ACGIH TLV:15 MG/M3

Ingred Name:SULFUR  
CAS:7704-34-9  
RTECS #:WS4250000  
Fraction by Wt: 1%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES  
Health Hazards Acute  
and Chronic:EYE: CAN CAUSE SEVERE IRRITATION &  
POTENTIAL PERMANENT INJURY. SKIN : PROLONGED OR REPEATED CONTACT  
CAN CAUSE CHRONIC SORES. BREATHING: VAPOR CAN CAUSE IRRITATION.  
INGESTION: CAN CAUSE DIGESTIVE SYSTEM BURNS.  
Explanation of Carcinogenicity:SODIUM BICHROMATE IS CLASSIFIED AS A  
HUMAN CARCINOGEN BY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
(IARC).  
Effects of Overexposure:EYE AND SKIN IRRITATION.  
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15  
MINUTES. SKIN: REMOVE ALL CONTAMINATED CLOTHING. RINSE SKIN WITH  
COPIOUS AMOUNT OF WATER, AND WASH WITH SOAP AND WATER. INGESTION:  
OBTAIN SERVICES OF A PHYSICIAN, AND CALL POISON CONTROL CENTER IN  
YOUR AREA. INDUCE VOMITING.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL, FOAM, WATER SPRAY, CARBON DIOXID

E.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS, AND PROTECTED CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE OR CONTAIN SPILL WITH EARTH, FLOOR DRY, SAND, ETC. ABSORB SPILL WITH APPROPRIATE ABSORBENT. TRANSFER CONTAMINATED ABSORBENT AND DIKING MATERIAL INTO CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. DO NOT STORE ABOVE 120F.

Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID BREATHING VAPORS. WEAR A NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES IF EXPOSURE LIMITS ARE EXCEEDED.

Ventilation:NORMAL VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:IMPERVIOUS GLOVES (NEOPRENE RUBBER)

Eye Protection:

WEAR CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:WASH HANDS BEFORE EATING, DRINKING, SMOKING OR USING BATHROOM.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres: