View NSN Online: https://aerobasegroup.com/nsn/9150-00-458-0075

OMNITECH INTERNATIONAL INC -- VV-L-800C LUBRICATING OIL, GENERAL PURPOSE 9150-00-458-0075

============= Product Identification =================

Product ID: VV-L-800C LUBRICATING OIL, GENERAL PURPOSE

MSDS Date:07/01/1992

FSC:9150

NIIN:00-458-0075

MSDS Number: BNQBB === Responsible Party ===

Company Name: OMNITECH INTERNATIONAL INC

Address:800 N ACADIA RD

City:THIBODAUX

State:LA ZIP:70301 Country:US

Info Phone Num:5

04-446-2003 FAX: 504-446-7546 Emergency Phone Num:504-446-2003

CAGE:KO342

=== Contractor Identification ===

Company Name: OMNITECH INTERNATIONAL INC

Address:800 N ACADIA RD

City:THIBODAUX

State:LA ZIP:70301 Country:US

Phone:504-446-2003

CAGE:KO342

Company Name: QPL INC, FORMERLY OMNITECH INTERNATIONAL, INC.

Address:800 N. ACADIA ROAD

Box:City:THIBODAUX

State:LA ZIP:70301 Country:US

Phone:504-394-8440

CAGE:0AD61

======= Composition/Information on Ingredients ========

Ingred Name:LIG

HTWEIGHT OIL Fraction by Wt: 92%

Other REC Limits: NONE SPECIFIED

Ingred Name: CORROSION INHIBITOR IN GREASE (ALOX-2201)

Fraction by Wt: 6%

Other REC Limits: NONE SPECIFIED

Ingred Name: THERMO SETTING ACRYLIC PLASTICIZER

Fraction by Wt: 1%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3

Ingred Name: FOOD-GRADE ANTIOXIDANT

Fraction by Wt: 0.5%

Other REC Limits: NONE SPECIFIED

Ingred Name:SURFACTANT (NON-IONIC)

Fraction by Wt: 0.5%

Other REC Limits: NONE SPECIFIED

============

==== Hazards Identification ==========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO

Health Hazards Acute and Chronic:CENTRAL NERVOUS SYSTEM DEPRESSION, EYE/SKIN IRRITATION.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC OR NTP AS A CARCINOGEN.

Effects of Overexposure: EYES-REDNESS, TEARING, BLURRED VISION. SKIN-REDNESS, HEADACHE, POSSIBLE ASPHYXIATION, HEART IRREGULARITIES.

INGESTION- NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:PRE-EXISTING DERMATITIS, PRE-EXISTING HEART CONDITION.

First Aid:SKIN AND EYE: FLUSH AFFECTED AREA WITH COOL WATER FOR 15 MINUTES-GET MEDICAL AID. INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NOT BREATHING. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

======= Fire Fighting Measures

=======================================
Flash Point Method:TCC
Flash Point:295F,146C Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:USE WATER SPRAY TO COOL AEROSOL CANS. USE SMOTHERING TECHNIQUE FOR EXTINGUISHING BECAUSE OF OIL CONTENT, DO NOT USE WATER ON OIL FIRES.
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEGREES F (49 DEGREES C).
======================================
Spill Release Procedures:REMOVE HEAT OR IGNITION SOURCES. COLLECT LIQUID WITH ABSORBENT MATERIAL. DO NOT FLUSH TO SEWER OR SURFACE WATER.
============ Handling and Storage =============
Handling and Storage Precautions:USE SAFETY GOGGLES, PROPER RESPIRATORY PROTECTION AND ADEQUATE VENTILATION. Other Precautions:WRAP EMPTY CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN TRASH.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL EXHAUST: USE TO KEEP EXPOSURE BELOW TLV. MECHANICAL (GENERAL): EXPLOSION - PROOF FAN. Protective Gloves:NEOPRENE OR RESISTANT GLOVES. Eye Protection:SAFETY GOGGLES.
Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS. SAFETY SHOWER AND EYE BATH. Work Hygienic Practices:READ LABEL CAREFULLY BEFORE USING PRODUCT.
Supplemental Safety and Health

======== Physical/Chemical Properties =========

=====

HCC:V2

Boiling Pt:=293.3C, 560.F Vapor Pres:5 MMHG Vapor Density:>AIR Spec Gravity:>1

Evaporation Rate & Deference: SLOWER THAN ETHER

Solubility in Water: NEGLIGIBLE

Appearance and Odor: AMBER LIQUID CONCENTRATE - PETROLEUM ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

particular situation.

Stability Condition to Avoid:DO NOT STORE IN AREAS OF OPEN FLAMES OR HIGH TEMPERATURE.

Hazardous Decomposition Products:

CARBON MONOXIDE, CARBON DIOXIDE,

SULFUR DIOXIDE, HYDROGEN CHLORIDE, PHOSGENE, HYDROGEN FLUORIDE.

Conditions to Avoid Polymerization: STRONG OXIDIZING AGENTS, HEAT, SPARKS, FLAMES.

====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF THROUGH A LICENSED WASTE DISPOSAL COMPANY. FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by e lements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their