

NICE-PAK PRODUCTS, INC. -- ISOPROPYL ALCOHOL AND WATER -- 6810-00-655-8366

=====
Product Identification
=====

Product ID:ISOPROPYL ALCOHOL AND WATER

MSDS Date:03/29/1991

FSC:6810

NIIN:00-655-8366

MSDS Number: BNQBW

=== Responsible Party ===

Company Name:NICE-PAK PRODUCTS, INC.

Address:TWO NICE-PAK PARK

City:ORANGEBURG

State:NY

ZIP:10962-1376

Country:US

Info Phone Num:914-365-1700

Emergency Phone

Num:914-365-1700

Preparer's Name:B. HANNAN

CAGE:59825

=== Contractor Identification ===

Company Name:PDI - PROFESSIONAL DISPOSABLES, INC DIV OF NICE-PAK
PRODUCTS

Address:2 NICE-PAK PARK

Box:City:ORANGEBURG

State:NY

ZIP:10962-1376

Country:US

Phone:914-365-1700

CAGE:59825

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGI

=====
=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 5840 MG/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: OVEREXPOSURE MAY LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION, LEADING TO HEADACHES AND DIZZINESS. EYE: MAY LEAD TO IRRITATION AND WILL INJURE EYE TISSUE IF NOT REMOVED PROMPTLY. SKIN: MAY LEAD TO DERMATITIS. INGESTION: MAY LEAD TO VOMITING. CHRONIC: PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.
Explanation of Carcinogenicity:THIS CHEMICAL IS NOT LISTED AS HAVING ANY EVIDENCE OF BEING CARCINOGENIC.
Effects of Overexposure:OVEREXPOSURE MAY LEAD TO DIZZINESS, HEADACHES, DERMATITIS AND EYE IRRITATION. HIGH VAPOR CONCENTRATIONS ARE ANESTHETIC AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS, SUCH AS LIGHTHEADEDNESS, HEADACHE AND DIZZINESS.
Medical Cond Aggravated by Exposure:PERSONS WITH SKIN, HEART, RESPIRATORY, OR ANY OTHER MEDICAL CONDITION SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

=====
=====
===== First Aid Measures =====
=====

First Aid:SKIN: IMMEDIATELY FLUSH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF NECESSARY. INHALATION: IMMEDIATELY REMOVE VICTIM TO FRESH AIR. GIVE CPR IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
INGESTION: GET PROMPT MEDICAL ATTENTION. DO NOT INDUCE VOMITING. KEEP AT REST.

=====
=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC
Flash Point:78.0F,25.6C
Lower Limits:2.0
Upper Limits:12.0
Extinguishing Media:USE FOAM, OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/E

xplosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. VAPORS HEAVIER THAN
AIR, CAN TRAVEL ALONG GROUND AND FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE. ELIMINATE IGNITION SOURCES. ABSORB
MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL.
PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED WORK AREA.
KEEP CONTAINERS CLOSED WHEN NOT IN USE. FLAMMABLE LIQUID. DO NOT
STORE ABOVE 120F.

Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL,
GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC
ELECTRICITY, OR OTHER SOURCES OF IGNITION. EXPLOSION HAZARD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH
/MSHA APPROVED

RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR
CARTRIDGES IF TLV IS EXCEEDED.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN
ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:SAFETY SHOES, EYE WASH STATION AND SAFETY
SHOWER.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WAS

H SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:190F,88C

Vapor Pres:25

Vapor Density:1.6

Spec Gravity:0.87

Evaporation Rate & Reference:>1 (BUTYL ACETATE = 1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS LIQUID, ALCOHOL ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, REACTIVE ALKALI METALS.

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION. ALSO AVOID VAPOR ACCUMULATION.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF ALL WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.